





Advanced High-Speed Bluetooth USB 2.0 Adapter

TBW-104UB(V2.1R)

The USB 2.0 Bluetooth Adapter allows you to make wireless short-range connections between your computer and Bluetooth-enabled devices.. This Bluetooth v2.0 utilizes Enhanced Data Rate (EDR) to allow for data rates up to 3Mbps. The Bluetooth adapter can easily connect to your Bluetooth-enabled devices from up to 100 meters away.

FEATURES

- Compliant with Bluetooth v2.0 Specification with EDR (Enhanced Data Rate) support
- Backward compatible with Bluetooth v1.1 and v1.2 devices
- Support Full-Speed Bluetooth operation with Full Piconet support
- Support AFH (Adaptive Frequency Hopping) and Fast Connection
- Up to 3Mbps Access Data Rate and Low Power Consumption
- Compatible with Windows 2000/XP/Vista & MCE (Media Center Edition) Operating Systems
- Enable computers to connect Bluetooth enabled devices such as printers, headset, audio/video, basic Image, PDAs, and mobile phones
- Compliant with Class I Bluetooth Operations
- Communicates wirelessly up to 100 meters (328 ft.) (depends on the environment)
- Trouble free Plug-n-Play Installation
- 2-Year Warranty

Advanced High-Speed Bluetooth USB 2.0 Adapter TBW-104UB(V2.1R)

SPECIFICATIONS

Hardware		
Standards	Class I Bluetooth v2.0 with EDR Backward Compatible with Bluetooth v1.1, v1.2 USB 1.1, 2.0	
Antenna	External Dipole Antenna	
Supported OS	Windows 2000/XP/Vista & MCE	
Power Consumption	Typical: 95mA; Idle: 12mA	
Dimensions	• 71.25 x 35.60 x 11.25 mm (2.8 x 1.4 x 0.44 in.)	
Weights	• 10 g (0.35 oz.)	
Temperature	• Operating: 0° ~ 50° C (32° ~ 122° F) • Storage: -20° ~ 70° C (-4° ~ 158° F)	
Humidity	• 10~90%	
Emissions	• CE, FCC	
Bluetooth		
Frequency	• 2.400 ~ 2.483.5 GHz	
Spread Spectrum	Frequency Hopping and Adaptive Frequency Hopping	
Module Technique	GFSK, DQPSK(2Mbps) and 8DPSK(3Mbps)	
	DUN (Dial-up Networking), FAX LAP (LAN Access Profile), SPP (Serial Port Profile)	
Profile Support	HID (Human Interface Device), HCRP (Hardcopy Cable Replacement Profile)	
	FTP (File Transfer Profile), OPP (Object Push Profile)	
	A2DP (Advanced Audio Distribution Profile), GAVDP (Generic Audio/Video Distribution Profile)	
	HSP (Headset Profile), PAN (Personal Area Networking) BIP (Basic Image Profile), SYNC (Synchronization Profile)	
	AV (Audio Video), GOEP (Generic Object Exchange Profile)	
RF Output Power	17dBm (typical)	
Receiving Sensitivity	-90dBm@0.1%BER (typical)	
Data Rate	• Up to 3Mbps	
Data Range	Up to 100m (328 ft.) depends on environment	

NETWORKING SOLUTIONS



PACKAGE CONTENTS

- TBW-104UB
- Quick Installation Guide
- CD-ROM (Driver/User's Guide)
- USB Cable (15cm/6 in)

RELATED PRODUCTS

TVP-SP1BK	ClearSky ™ Bluetooth VoIP Phone Kit (for Skype™)
TBW-103UB	802.11g Wireless & Bluetooth Combo USB Adapter
TBW-102UB	High-Power Wireless Bluetooth USB Adapter

ORDERING INFORMATION

TRENDNET

20675 Manhattan Place, Torrance, CA 90501 USA

Tel: 1-310-961-5500 Fax: 1-310-961-5511 Web: www.trendnet.com Email: sales@trendnet.com

To Order Please Call:

1-888-326-6061



Headset