



Mini-GBIC Dual Wavelength Single-Mode LC Module 1310/1550 Pair

TEG-MGBS10D3, TEG-MGBS10D5, TEG-MGBS40D3, TEG-MGBS40D5

The pair of Mini-GBIC Single Mode module works with standard Mini-GBIC slots on most switches. The pair of Dual Wavelength Single Mode LC Type modules must be used together in order to span distances up to 10km (6.2 miles). Two modules are included, each with 1 x 1000Mbps-LX (LC Simplex -Type) Mini-GBIC connector.

- ### FEATURES
- Compliant with IEEE 802.3z Gigabit Ethernet and Fiber Channel Standards
 - Compliant with SFP MSA, SONET/SDH standards, Class 1 laser products, EN 60825, and EN60950
 - Metal Enclosure, low EMI
 - Simplex LC connector
 - Hot Pluggable and Low Power Dissipation
 - Single 3.3V Power Supply Voltage

Mini-GBIC Dual Wavelength Single-Mode LC Module 1310/1550 Pair

TEG-MGBS10D3, TEG-MGBS10D5, TEG-MGBS40D3, TEG-MGBS40D5

SPECIFICATIONS

Model Name	Wavelength	Power Budget	Sensitivity	Power	Distance
TEG-MGBS10D3	TX: 1310nm RX: 1550nm	11dBm	-20	-9 ~ -3dBm	10km
TEG-MGBS10D5	TX: 1550nm RX: 1310nm	11dBm	-20	-9 ~ -3dBm	10km
TEG-MGBS40D3	TX: 1310nm RX: 1550nm	20dBm	-23	-3 ~ +3dBm	40km
TEG-MGBS40D5	TX: 1550nm RX: 1310nm	20dBm	-23	-3 ~ +3dBm	40km

Application

- Metro Access Rings
- Point-to-Point Networking
- Suitable for Fast Ethernet and OC-12
- 3-years limited warranty

Contact Information

TRENDNET[®]

20675 Manhattan Place, Torrance, CA 90501 USA

Tel: 1-310-961-5500

Fax: 1-310-961-5511

Web: www.trendnet.com

Email: sales@trendnet.com

Pour commander, merci d'appeler au:

1-888-326-6061

