



10-Bay Fiber Chassis **TFC-1000 (v1.0R)**

This 10-Bay Fiber chassis provides housing for up to 10 fiber converters. Designed for the TFC-210 and TFC-2000 series fiber converters, the chassis is equipped with a cooling fan and built-in power supply. This fiber chassis allows you to organize multiple fiber converters to a single device.

FEATURES

- Supports up to 10 TFC-210 or TFC-2000 series fiber converters
- Single Internal cooling fans
- Diagnostic LED
- Plug & Play; Hot-Swappable
- Standard 19" rack-mount design (3U)
- 5-year Warranty

10-Bay Fiber Chassis

TFC-1000 (v1.0R)

SPECIFICATIONS

Hardware	
Interface	• 10-Bay of Housing for up to 10 TFC-210 or TFC-2000 Series Fiber Converter
Diagnostic LED	• Power
Power	• 100 ~ 240 VAC, 50/60Hz, Internal Power Supply
Power Consumption	• 90 Watts
Dimensions	• 440 x 266 x 133mm (17.32 x 10.47 x 5.24in)
Weight	• 6.4kg (14.2 lb)
Temperature	• Operating : 0°C ~ 45°C (32°F ~ 113°F) • Storage : -40°C ~ 70°C (-40°F ~ 158°F)
Humidity	• 5% ~ 90% RH
Certification	• CE, FCC

PACKAGE CONTENTS

- TFC-1000 Fiber Chassis
- Multi-Language Quick Installation Guide
- Power Cord
- Mounting Brackets
- Rack Mount Kit

RELATED PRODUCTS

TFC-210MSC	10/100Base-TX to 100Base-FX Multi-Mode SC-Type Fiber Converter
TFC-210MST	10/100Base-TX to 100Base-FX ST -Type Multi-Mode Fiber Converter
TFC-210S30	10/100Mbps-TX to 100Base-FX SC-Type Single-Mode Fiber Converter
TFC-210S20D3/D5	10/100Mbps-TX to 100Base-FX Dual-Wavelength Single-Mode Fiber Converter
TFC-2000MSC	1000Base-TX to 1000Base-SX SC-Type Multi-Mode Fiber Converter
TFC-2000S20/S50	1000Base-T to 1000Base-LX SC-Type Single-Mode Fiber Converter
TFC-2000S10D3/D5	1000Mbps-TX to 1000Mbps-LX WDM SC Fiber Converter

ORDERING INFORMATION

TRENDnet®

20675 Manhattan Place, Torrance, CA 90501 USA
Tel: 1-310-961-5500
Fax: 1-310-961-5511
Web: www.trendnet.com
Email: sales@trendnet.com

To Order Please Call:

1-888-326-6061

