

TK-210K

2-Port USB and PS/2 KVM Switch with Audio

TRENDnet's TK-210K 2-port USB and PS/2 KVM Switch with Audio & Microphone kit lets you control 2 USB enabled multimedia PCs with just one keyboard, monitor, mouse, microphone, and a set of speakers. TK-210K not only allows you to share your monitor, keyboard and mouse, but with the build-in 2-port USB hub, you can also share up to two USB devices. With just a simple press of a button, you can select the PC that you would like to operate, eliminating the hassle of cable swapping between 2 PCs. TRENDnet's TK-210K UAM comes with a 2-port USB KVM switch and two sets of cables. With it's Hot-Plug, Auto-Scan, Audible Feedback and Hot-Key operating features, the TK-210K UAM is the perfect choice for managing 2 PCs.



CRENDne

TRENDware, USA

What's Next in Networking

FEATURES

- Use one keyboard, monitor, and mouse to control two computers
- --- PS/2 and USB Keyboard/Mouse emulations
- --- 2-Port KVM Switch in compact size design
- *** Built-in 2-Port USB 1.1 Hub for sharing USB devices
- --- UHCI, OHCI USB interface support
- --- Support very High Video Quality, up to 1920 x 1440
- ••• Includes two sets of KVM, USB, and Audio & Microphone cables
- Supports computers with Windows 95/98/NT/ME/2000/XP, and Linux
- --- Multi-platform support for PC and Macintosh G3 / G4 / iMac
- ---- Hot-Plug feature; add PCs or remove connected PCs for maintenance without powering down the KVM switch or other PC's
- No software required, easy PC selection via Push Button or Hot-Keys
- --- Auto-Scan Mode for monitoring PCs
- --- LED display for easy status monitoring
- --- Beeping sound for port switching confirmation
- --> 1-Year Warranty

BENEFITS

--- Integration Friendly:

Does not require driver/software for the installation and operation. Switching between PCs with the push button or Hot-Key operation.

---> Flexible:

Hot-Plug feature, add PCs or remove connected PCs without powering off the KVM switch or the other PCs.

--- Cost Effective:

Manage two PCs with single keyboard, monitor, mouse and speakers/microphone; and share USB devices. Save on equipment cost, utility, and space.

---> Performance:

Support very High Video Quality up to 1920 x 1440. Keyboard status is saved for each PC.

SPECIFICATIONS

PC Port Connectors:

- 2 x USB Type B female port
- 2 x VGA HDB15 (15-pin) female connector
- 2 x 3.5mm audio jack
- 2 x 3.5mm microphone jack

Console Port Connectors:

- 2 x USB Type A female port
- 1 x PS/2 keyboard 6-pin mini-DIN female
- 1 x PS/2 mouse 6-pin mini-DIN female
- 1 x VGA HDB15 (15-pin) female
- 1 x 3.5mm audio jack
- 1 x 3.5mm microphone jack

KVM Cable:

- 2 x 3-in-1 KVM cable (male to male), 1.2 meters (4 feet)
- 2 x USB A-B cable (male to male),1.2 meters (4 feet)
- 2 x Audio+Microphone cable, 1.2 meters (4 feet)

VGA Resolution:

• 1920 x 1440

Port Selection:

Push Buttons and Hot-Keys

Auto-Scan Intervals:

• 10 seconds (non-adjustable)

Power Supply:

- Powered via PS/2 or USB Interface.
- Optional 9V DC, 500mA adapter

Dimensions (L x W x H):

• 137 x 88 x 44 mm (5.39 x 3.46 x 1.73 inches)

Weight:

• 295 g. (10.5 Oz.)

Temperature:

- Operating: 0° ~ 40°C (32° ~104° F)
- Storage: -20° ~ 60°C (-4° ~ 140° F)

Humidity:

• 0%~90% RH, Non-Condensing

Emissions:

• FCC, CE







TWORKING SOLUTIONS



To Order Please Call: 1-888-326-6061

RELATED PRODUCT

- *** TK-210K: 2-Port USB and PS/2 KVM Switch with Audio
- *** TK-205i: 2-Port KVM Switch with Integrated KVM
- *** TK-200K: 2-Port KVM Switch Kit
- *** TK-400K: 4-Port KVM Switch Kit
- *** TK-401R: 4-Port Rack Mount KVM Switch
- *** TK-801R: 8-Port Rack Mount KVM Switch
- *** TK-802R: 8-Port Stackable Rack Mount KVM Switch (with OSD)

ORDERING INFORMATION

TRENDware International, Inc.

3135 Kashiwa Street Torrance, CA. 90505. USA Tel: 310-891-1100

Fax: 310-891-1111 Web: www.TRENDNET.com Email: sales@trendware.com

