



2-Port USB Hub and PS/2 KVM Switch with Audio

TK-210K

TRENDnet's TK-210K 2-port USB and PS/2 KVM Switch with Audio & Microphone kit lets you control 2 USB enabled multimedia PCs with just one keyboard, monitor, mouse, microphone, and a set of speakers. TK-210K not only allows you to share your monitor, keyboard and mouse, but with the built-in 2-port USB hub, you can also share up to two USB devices. With just a simple press of a button, you can select the PC that you would like to operate, eliminating the hassle of cable swapping between 2 PCs. TRENDnet's TK-210K comes with a 2-port USB KVM switch and two sets of cables. With its Hot-Plug, Auto-Scan, Audible Feedback and Hot-Key operating features, the TK-210K is the perfect choice for managing 2 PCs.

FEATURES

- Use one keyboard, monitor, and mouse to control two computers
- PS/2 and USB Keyboard/Mouse emulations
- 2-Port KVM Switch in compact size design
- Built-in 2-Port USB 1.1 Hub for sharing USB devices
- UHCI, OHCI USB interface support
- Support very High Video Quality, up to 1920 x 1440
- Includes two sets of KVM, USB, and Audio & Microphone cables
- Supports computers with Windows 95/98/NT/ME/2000/XP/Vista, and Linux
- Multi-platform support for PC and Macintosh G3 / G4 / iMac
- Hot-Plug feature; add PCs or remove connected PCs for maintenance without powering down the KVM switch or other PC's
- No software required, easy PC selection via Push Button or Hot-Keys
- Auto-Scan Mode for monitoring Pcs
- LED display for easy status monitoring
- Beeping sound for port switching confirmation
- 2-Year Warranty

2-Port USB Hub and PS/2 KVM Switch with Audio TK-210K

SPECIFICATIONS

Hardware	
PC Port Connectors	<ul style="list-style-type: none"> • 2 x USB Type B female port • 2 x 3.5mm audio jack • 2 x VGA HDB15 (15-pin) female connector • 2 x 3.5mm microphone jack
Console Port Connectors	<ul style="list-style-type: none"> • 2 x USB Type A female port • 1 x PS/2 keyboard 6-pin mini-DIN female • 1 x PS/2 mouse 6-pin mini-DIN female • 1 x VGA HDB15 (15-pin) female • 1 x 3.5mm audio jack • 1 x 3.5mm microphone jack
KVM Cable	<ul style="list-style-type: none"> • 2 x 3-in-1 KVM cable (male to male), 1.2 meters (4 feet) • 2 x USB A-B cable (male to male), 1.2 meters (4 feet) • 2 x Audio+Microphone cable, 1.2 meters (4 feet)
VGA Resolution	• 1920 x 1440
Port Selection	• Push Buttons and Hot-Keys
Auto-Scan Intervals	• 10 seconds (non-adjustable)
Power Supply	• Powered via PS/2 or USB Interface. Optional 9V DC, 500mA adapter
Dimensions (L x W x H)	• 137 x 88 x 44 mm (5.39 x 3.46 x 1.73 inches)
Weight	• 295 g. (10.5 Oz.)
Temperature	• Operating: 0° ~ 40°C (32° ~104° F) • Storage: -20° ~ 60°C (-4° ~ 140° F)
Humidity	• 0%~90% RH, Non-Condensing
Emissions	• FCC, CE

NETWORKING SOLUTIONS



RELATED PRODUCTS

TK-210K	2-Port USB and PS/2 KVM Switch with Audio
TK-205i	2-Port KVM Switch with Integrated Cables
TK-200K	2-Port KVM Switch Kit
TK-400K	4-Port KVM Switch Kit
TK-401R	4-Port Rack Mount KVM Switch
TK-801R	8-Port Rack Mount KVM Switch
TK-802R	8-Port Stackable Rack Mount KVM Switch with OSD

ORDERING INFORMATION

TRENDnet®

20675 Manhattan Place, Torrance, CA 90501 USA
 Tel: 1-310-961-5500
 Fax: 1-310-961-5511
 Web: www.trendnet.com
 Email: sales@trendnet.com

To Order Please Call:

1-888-326-6061

