



4-Port USB KVM Switch Kit w/ Audio

TK-409K (v1.3R)

- 4-port KVM switch with VGA and USB connections to computers and audio devices
- Listen to music from one computer while working on the other
- High quality 2048 x 1536 resolution for a crisp display
- Supports most operating systems and advance mouse designs
- All required cabling included

The 4-Port USB KVM Switch with Audio lets you manage 4 computers with just one set of keyboard, monitor, mouse, and a set of speakers / microphone. The device comes with 4 sets of USB KVM and audio cables, no additional equipment required. Its compact size makes it ideal for home and business environment.

- Control up to 4 computers/servers with one set of console device
- USB keyboard/mouse emulation with 4 sets of detachable KVM cables
- Compliant with Windows and Linux
- High video quality, up to 2048 x 1536 VGA resolution
- Multi-Platform supports for PCs, Macintosh G3/G4/G5, iMac and Mac Mini
- Listen to music from one computer while working on the other
- Auto-Scan & LED display for computer monitoring
- Computer selection by face panel push buttons, keyboard hot key commands or Windows-based client switching software*
- User definable hot key (Windows only)
- Plug & Play and hot-pluggable
- USB interface power method
- 2-year limited warranty

Specifications

Hardware

Connections

- 4 computers

USB Interface

- USB 1.1 compliant

KVM Cable

- 2 sets of 1.2 m (4 ft.) KVM cables
- 2 sets of 1.8 m (6 ft.) KVM cables
- 2 sets of 1.2 m (4 ft.) audio cables
- 2 sets of 1.8 m (6 ft.) audio cables
- Cable Interface (all male)

KVM Cable

- To KVM
 - 1 x VGA/SVGA HDB 15-pin
- To Computer
 - 1 x USB (type A)
 - 1 X VGA/SVGA HDB 15-pin
- Audio Cable
 - To KVM
 - 1 x 3.5 mm speaker jack
 - 1 x 3.5 mm microphone in jack
 - To Computer
 - 1 x 3.5 mm speaker jack
 - 1 x 3.5 mm microphone jack

PC Port Connectors (all female)

- 4 x VGA/SVGA HDB 15-pin
- 4 x 3.5 mm speaker jack
- 4 x 3.5 mm microphone jack

Console Port Connectors (all female)

- 1 x USB Keyboard (type A)

- 1 x USB Mouse (type A)
- 1 x VGA/SVGA HDB 15-pin
- 1 x 3.5 mm speaker jack
- 1 x 3.5 mm microphone jack

Supported OS

- Windows and Linux

Port Selection

- Front panel push buttons, keyboard hot key commands or Windows-based client switching software*

Auto-Scan Interval

- 10 ~ 60 seconds

Keyboard Status

- Save and restore

Power Type

- USB interface power

Dimensions

- 167 x 80 x 28 mm (6.6 x 3.2 x 1.1 in.)

Weight

- 185 g (6.5 oz.)

Temperature

- Operating: 0°C ~ 40°C (32°F ~104°F)
- Storage: -20°C ~ 60°C (-4°F ~140°F)

Humidity

- Max 90%, non-condensing

Certifications

- CE, FCC

Package Contents

- TK-409K
- Quick Installation Guide
- 4 sets of USB KVM cables (2 x 1.2 m / 4 ft., 2 x 1.8 m / 6 ft.)
- 4 sets of audio cables (2 x 1.2 m / 4 ft., 2 x 1.8 m / 6 ft.)

*For optimal performance, we recommend using a wired keyboard and mouse. Please go to <http://www.trendnet.com/downloads> to download the client switching software.