

TPE-101I Power over Ethernet (PoE) Injector

TRENDnet

TRENDware, USA

What's Next in Networking

TRENDnet's TPE-101I Power over Ethernet Injector provides an innovative and cost effective solution to a variety of Ethernet devices such as VoIP phones or Wireless Access Points. Reduce costs by using existing CAT5 cable to deliver both power and data where power source is difficult to obtain.



FEATURES

- IEEE 802.3af Power over Ethernet (PoE) Standard Compliant
- Reduce Cabling for Wireless APs, IP Phone and any IEEE 802.3af Powered Device (PD)
- *** Supplies Power to PD up to 15.4 watts per
- Automatically detecting PoE Terminals and Supplying Inline Power
- Advanced Auto-Sensing Algorithm Giving Power only to 802.3af end device
- High Safety Standards with Short Circuit Protection
- Auto Disconnection for Over Voltage or Under Voltage Situation
- *** Supports Power Detection and Classification
- ** 5-Year Warranty



TPE-101I Power over Ethernet (PoE) Injector

SPECIFICATIONS

Hardware Standard:

- IEEE 802.3 10Base-T
- IEEE802.3u 100Base-TX
- IEEE 802.3af Power Over Ethernet

Network Media:

- 10Mbps: Cat 3,4,5 Unshielded/Shielded/Screened Cable
- 100Mbps: Cat 5, 5E, 6 Unshielded/Shielded/Screened Cable

Protocol:

CSMA/CD

Topology:

• Star

Ports:

- 1 x DATA-IN Port (Data only)
- 1 x POE-OUT Port (Data + Power)

Power:

- Input: 48V 0.5A
- Output: Class 0, 48V DC @ 15.4 watts; Class 1, 48V DC @ 4 watts; Class 2, 48V DC @ 7 watts; Class 3, 48V DC @ 15.4 watts

Diagnostic LEDs:

- Power (Green)
- Power Good (Green)

Power Consumption:

• 24 watts (max)

Temperature:

- Operation: 0 ° C~40 ° C (32 ° F~ ° F)
- Storage: -10 ° C~70 ° C (° F~ ° F)

Humidity:

10%- 90% (non-condensing)

Dimensions (LxWxH):

• 87 x 85 x 24mm (3.425 x 3.35 x 0.95 inches)


Weight:


• 156g (0.35 lb)

Certifications:

• FCC. CE







To Order Please Call: 1-888-326-6061

RELATED PRODUCT

- *** TPE-102S: Power over Ethernet (PoE) Splitter
- *** TPE-S88: 16-Port 10/100Mbps Web Smart PoE Switch

ORDERING INFORMATION

TRENDware International, Inc.

3135 Kashiwa Street Torrance, CA. 90505. USA Tel: 310-891-1100

Fax: 310-891-1111 Web: www.TRENDNET.com Email: sales@trendware.com

