





# **16-Port 10/100 Mbps PoE+ Switch** TPE-T160H (v1.0R)

- 16 x 10/100 Mbps PoE+ ports
- Up to 30 Watts per port with a 250 Watt total power budget
- 3.2 Gbps switching capacity
- Rack mount kit included
- Use with TRENDnet's PoE Splitter to network and power non-PoE devices
- · Limited lifetime warranty

The 16-Port 10/100 Mbps PoE+ Switch, model TPE-T160H, delivers data and power over existing Ethernet cables to Power over Ethernet (PoE) devices such as Access Points and IP Cameras. It supplies up to 30 Watts of power per port with a 250 Watt power budget. A convenient on/off button is located on the back of the switch and a rack mount kit is included.



# **Hardware**



# PoE+

Supplies up to 30 Watts of PoE power per port with a 250 Watt power budget



### Ports 16 x 10/100 Mbps PoE+ ports



## **Switching Capacity** 3.2 Gbps switching capacity



## **Rack Mountable**

Rack mountable metal enclosure with included mounting kit




## On/Off Convenient on/off switch

# **LED Indicators**

LED indicators convey port status

# **Networking Solution**





# **Specifications**

#### Standards

- IEEE 802.3
- IEEE 802.3u
- IEEE 802.3x
- IEEE 802.3af (15.4 Watts/port)
- IEEE 802.3at (30 Watts/port)
- IEEE 802.3az

#### **Device Interface**

- 16 x 10/100 Mbps PoE/PoE+ Ports
- LED indicators
- Power switch

#### **Data Transfer Rate**

- Ethernet: 10 Mbps (half duplex), 20 Mbps (full duplex)
- Fast Ethernet: 100 Mbps (half duplex), 200 Mbps (full duplex)

#### Performance

- Data Ram Buffer: 1.25 MB
- Switch Fabric: 3.2 Gbps
- MAC Address Table: 4K entries
- Forwarding rate: 2.38 Mpps (64-byte packet size)

#### **Special Features**

- Rack mount kit included
- GREENnet energy saving technology

#### Power

- Internal Power Supply
- Input: 90-260 V AC, 50/60 Hz, 1 A
- Output: 48 V DC, 50/60 Hz, 0.6 A

#### Consumption

- Max.: 260 Watts
- PoE budget: 250 Watts

#### PoE+

• pin 1,2 for power+ and pin 3,6 for power- (mode A)

### **Operating Temperature**

•0-40 °C (32-104 °F)

#### **Operating Humidity**

• Max. 90% non-condensing

## Dimensions

• 440 x 220 x 44 mm (17.32 x 8.66 x 1.73 in.)

#### Weight

• 3.0 kg (6.6 lbs.)

#### Certifications

- CE
- FCC

#### Warranty

Limited lifetime warranty

### Package Contents

- TPE-T160H
- Quick Installation Guide
- Power cord
- Rack mount kit

TRENDnet offers a limited lifetime warranty for all of its metal-enclosed network switches that have been purchased in the United States/Canada on or after 1/1/2015. Cooling fan and internal power supply carry a one-year warranty.



20675 Manhattan Place • Torrance • CA 90501 • USA • T: 1- 888-326-6061 • F: 1-310-961-5511 • sales@trendnet.com • www.TRENDnet.com TRENDnet is a registered trademark. Other Brands and product names are trademarks of their respective holders. Information provided in this document pertain to TRENDnet products and is subject to change at any time, without notice. For the most recent product information please visit <a href="http://www.trendnet.com">http://www.trendnet.com</a> Copyright © TRENDnet. All Rights Reserved