





2.5" USB 3.0 External Enclosure TU3-S25 (V1.OR)

The 2.5" USB 3.0 External Enclosure, model TU3-S25, supports one 2.5" SATA I or II hard disk drive with storage capacities in excess of 1 Terabyte (hard drive sold separately). Store and transfer content at blazing fast 5Gbps USB 3.0 speeds—10 times faster than USB 2.0.

Install a SATA I or II hard drive and connect the enclosure to a 5Gbps USB 3.0 port on your computer. USB 3.0 is backward compatible with USB 2.0 ports. An aluminum housing cools the enclosed hard drive and there is a convenient power button on the front of the enclosure. Save time by transfering large files at breakthrough 5Gbps USB 3.0 speeds.

SETUP INFO •1 x USB 3.0 Type Mini-B port

- Backwards compatible with USB 2.0, 1.1, and 1.0 connections
- Supports all USB speeds: Super speed (USB 3.0: 5Gbps*), High speed (USB 2.0: 480Mbps), Full speed (USB 1.1: 12Mbps), and Low speed (USB 1.0: 1.5Mbps)
- Supports one 2.5" SATA/SATA II hard drive or Solid State Drive (SSD)
- Maximum hard drive capacity supported: 2TB
- Compatible with Windows, Mac, and Linux operating systems**
- · Data transfer LEDs
- Light weight aluminum housing
- · Sleek and small external enclosure
- · Plug and play support with no driver installation required
- 2-year limited warranty

*Data is transferred over USB 3.0 connections at up to 5Gbps. However actual data throughput may be significantly affected by choice of hard drive, computer system architecture, CPU loading, and other factors.


**USB 3.0 super speeds are based on compatible operating systems.



SPECIFICATIONS

Hardware			
USB Standards	USB 3.0 Backwards compatible with USB 2.0, 1.1, and 1.0		
External Ports	• 1 x USB 3.0 Type Mini-B port		
HD Interface	• 1 x SATA/SATA II		
Compatible drives	• 2.5 in. HDD or SSD		
HD Capacity	• 2TB (max.)		
Supported OS	Windows 7 (32/64-bit), Vista (32/64-bit), XP (32/64-bit) Mac OS X v10.4 to 10.6** Linux		
Data Rates	• Super speed: 5Gbps* (USB 3.0) • High speed: 480Mbps (USB 2.0) • Full speed: 12Mbps (USB 1.1) • Low speed: 1.5Mbps (USB 1.0)		
HD Transfer Rates	SATA II: up to 3Gbps SATA I: up to 1.5Gbps		
Power Switch	• On/off		
Dimensions (L x W x D)	• 122 x 75 x 15 mm (4.8 x 3 x 0.6 in.)		
Weight	• 62.4 g (2.2 oz)		
Enclosure Material	Aluminum and PVC		
Temperature	• Operating: 10°C ~ 40°C (50°F ~ 104°F) • Storage: -10°C ~ 80°C (14°F ~ 176°F)		
Humidity	Max. 90% non-condensing		
Certifications	• CE, FCC		

PACKAGE CONTENTS



PACKAGE CONTENTS

• TU3-S25	
Multi-Language Quick Installation Guide	
• CD-ROM (User's Guide)	
USB 3.0 Type A to Type Micro-B cable(0.9 m / 3 ft.)	
Hard drive mounting screws	

RELATED PRODUCTS

TU3-H2PIE	2-Port USB 3.0 PCI Express Adapter
TU3-H2EC	2-Port USB 3.0 ExpressCard Adapter
TU3-S35	3.5" USB 3.0 External Enclosure

CONTACT INFORMATION

TRENDNET

20675 Manhattan Place, Torrance, CA 90501 USA Tel: 1-310-961-5500 Fax: 1-310-961-5511 Web: <u>www.trendnet.com</u> Email: sales@trendnet.com 1-888-326-6061