



Mini USB-C HD Docking Cube

TUC-DS1 (v1.0R)


- Extend or mirror your notebook PC's display to an HDTV via HDMI
- Supports up to 3840 x 2160 resolution at 30Hz
- Gigabit Ethernet Port
- HDMI audio support
- HD video over a high-speed USB-C connection
- One USB 3.0 port and two USB 2.0 ports
- Supports Windows 10 Continuum mode
- Compatible with most Android OS 7.0 and up phones with USB-C interface
- Supports Windows® 10 and Mac® operating systems

TRENDnet's Universal USB-C HD Docking Cube, model TUC-DS1, connects your laptop or Ultrabook[™] to your network and multiple devices with a single cable. Manage workstation devices such as USB storage, keyboard, mouse, printer, scanner, and HD display over a high-speed USB-C connection. Extend or mirror your notebook PC's display to an HDTV via HDMI to experience high definition video.









HDMI Port

Connect an HDMI monitor to the TUC-DS1 to add a high definition display to your workstation.

Compact Cube Design

Compact space saving design connects workstation peripherals over a single USB-C connection.

USB Ports

Convenient USB 2.0 and 3.0 ports allow you to connect multiple USB devices to your notebook PC.

Networking Solution







USB-C Docking Station

Build your ideal workstation by connecting all devices to the TUC-DS1 with a single high-speed USB-C connection.



HDMI Port

Connect an HDMI monitor to the TUC-DS1 to add a high definition display to your workstation.



HD Resolution

Supports up to 3840 x 2160 at 30Hz for PC, and up to 1920 x 1080 @ 60Hz for Windows Phone



Audio Support

HDMI Audio Support



USB Ports

One USB 3.0 port and two USB 2.0 ports for USB keyboard, mouse, storage, and other devices



Gigabit Port

Connect to the network with a high-performance gigabit port



Compact Cube Design

Compact space saving design connects workstation peripherals over a single USB-C connection



Easy Setup

Simple installation in minutes



Operating Systems

Compatible with Windows® 10 and Mac® operating systems



Specifications

opecinications	
Standards	• HDMI 1.4b • IEEE 802.3 • IEEE 802.3u • IEEE 802.3ab • IEEE 802.3az • USB 2.0 • USB 3.0
Interface	 1 x HDMI port 1 x Gigabit Ethernet port 1 x USB Type-C upstream port 1 x USB 3.0 downstream port 2 x USB 2.0 downstream ports 1 x Power jack
Supported OS	 Windows[®] 10, 8.1, 8, 7 Mac[®] 10.9 - 10.12 Android 7.0 (with USB-C connector)
HDMI	 HDMI: Max. 3840 x 2160 resolution (supports full 1080p) 5.1 Channel (over HDMI source)
Operating Temperature	• 0 – 40 °C (32 – 104 °F)
Operating Humidity	Max. 90% non-condensing
Power	 Input: 100 - 240 V AC, 50/60 Hz, 0.8 A Output: 5V DC, 4A external power adapter Max. consumption: 18.2W
Dimensions	• 65 x 59 x 35mm (2.6 x 2.3 x 1.4 in.)
Weight	• 130g (4.6 oz.)
Warranty	• 2 year limited
Certifications	• CE • FCC

PACKAGE CONTENTS

- TUC-DS1
- · Quick Installation Guide
- Power adapter (5V DC, 4A)
- USB-C cable (91cm/ 36 in.)