







Wireless N Firewall Router

TEW-631BRP (V3.0)

The Wireless N Broadband Router delivers the highest level of security, 12x the speed and 4x the range of wireless g products. StreamEngineTM technology allows you to seamlessly stream live media, download files, play games and talk Online all at the same time and with no jitter.

The latest in wireless encryption, a double firewall and a unique manual on/off wireless switch provides the ultimate in wired and wireless security. Advanced antenna technology eliminates dead spots. A quick and intuitive installation process, remote management capabilities and a 3-year warranty make this product well suited for your most demanding networking needs.

FEATURES

- Wi-Fi Compliant with IEEE 802.11n and IEEEE 802.11b/g Standards
- 4 x 10/100Mbps Auto-MDIX LAN Port and 1 x 10/100Mbps WAN Port (Internet)
- Supports cable/DSL modems with Dynamic IP, Static IP, PPPoE, PPTP, L2TP & BigPond connection types
- Supports AP mode and Bridge mode
- 3 external antennas support 300Mbps high speed performance and great coverage
- · Firewall features Network Address Translation (NAT), and Stateful Packet Inspection (SPI) protects against Dos attacks
- Traffic control with virtual servers, special applications, gaming services and Ubicom StreamEngine™ feature
- UPnP (Universal Plug & Play) and ALGs Support for Internet applications such as Email, FTP, Gaming, Remote Desktop, Net Meeting, Telnet, and more
- Stream Engine Technology by Ubicom™ provides QoS traffic prioritization of online games, VoIP calls, and streaming video to reduce lag time and jitter
- Universal Plug and Play (UPnP) and Application Level Gateway support for internet applications such as email, FTP, gaming, remote desktop, Net Meeting, telnet and more
- Provides Additional Security of Enable/Disable SSID, Access Control, Web & Inbound traffic filters
- Supports Multiple and Concurrent IPSec, L2TP and PPTP VPN Pass-Through Sessions
- · Easy management via Web browser (IE 6.0 or above, FireFox, Opera, Netscape) and remote management
- Supports 64/128-bit WEP(for 11b/g), WPA/WPA2 and WPA-PSK/WPA2-PSK
- Works with Windows 95/98/NT/2000/XP/2003 Server/Vista, Linux and Mac OS
- Coverage up to 150 meters (500ft.) Indoor(depends on the environment)
- Coverage up to 400 meters (1300ft.) Outdoor(depends on the environment)
- 3 year limited warranty
- Link to Wi-Fi certification: http://certifications.wi-fi.org/wbcs ViewCertificate.php?product_id=5877

Wireless N Firewall Router TEW-631BRP (V3.0)

SPECIFICATIONS

Hardware		
Standards	Wired: IEEE 802.3 (10Base-T), IEEE 802.3u (100Base-TX)	
	Wireless: IEEE 802.11b, IEEE 802.11g, IEEE 802.11n (draft 2.0)	
WAN	• 1 x 10/100Mbps Auto-MDIX Port (Internet)	
LAN	• 4 x 10/100Mbps Auto-MDIX Port	
Slide Switch	Turn On/Off Wireless LAN	
WPS Button	WPS configuration	
Connection Type	Dynamic IP, Static (Fixed) IP, PPPoE, PPTP, L2TP, BigPond	
	4K ~ 6K Configurable NAT entries; Restricted NAPT	
NAT Firewall	IP Ranges, Port Ranges & Schedule	
	Pre-Defined Game Hosting Configurations	
	Port Triggering for 24 Special Applications	
	ALG Support – RTP/RTSP, AOL, FTP, ICMP, WMP/MMS, NetMeeting, SIP	
	UP to 24 Rules	
SPI Firewall	Cyber Attack Protection – Verified Against Over 2000 Attacks	
WDS	Enable/Disable Wireless Distribution System support	
UPnP	UPnP IGD 1.0 Compliant	
DMZ	DMZ Host, 24 Configurable Virtual Servers & Game Servers	
DNO	Static or WAN assigned DNS Servers	
DNS	• 10 verified services for DDNS	
Internet Access Control	 Policy based parental control; time based internet access; port range/service filtering; Dynamic URL filtering; Internet domain restriction; 32 user defined schedules, 24 MAC address filter entries 	
Landan	3 types & 3 severities event logging; up to 1K entries	
Logging	Email report logging on schedule or log full	
LED Indicator	Power, LAN1~LAN4, WAN, WLAN	
Power Adapter	• 12V DC, 1A External Power Adapter	
Power Consumption	• 779mA	
Dimensions (LxWxH)	• 180 x 122 x 30 mm (6.8 x 4.6 x 1.1 inches)	
Weight	• 350g (0.8 lb)	
Tomporaturo	• Operating: 0° ~ 40° C (32° ~ 104° F)	
Temperature	• Storage: -20° ~ 60° C (-4° ~ 140° F)	
Humidity	Max. 90% (Non-Condensing)	
Emissions	• CE, FCC	

Wireless N Firewall Router TEW-631BRP (V3.0)

SPECIFICATIONS

Wireless		
Frequency	• 2.412 ~ 2.462 GHz (FCC)	
	• 2.412 ~ 2.472 GHz (ETSI)	
Antenna	3 x 4dBi Fixed Dipole Antenna	
Media Access Protocol	CSMA/CA with ACK	
Data Rate (auto fallback)	802.11b: 11Mbps, 5.5Mbps, 2Mbps, and 1Mbps	
	 802.11g: 54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 9Mbps and 6Mbps 	
	802.11n (draft) : up to 300Mbps	
Security	Encryption: Hardware AES/TKIP, 64/128-bit WEP (Hex/Passpharse, for 11b/g)	
	802.1X/EAP: EAP-TLE,EAP-TTLE/MSCHAPv2, PEAPv0/EAP-MSCHAPv2, PEAPv1/EAP-GTC	
	WPA: WPA/WPA2, WPA-PSK/WPA2-PSK (AES-11b/g/n, TKIP-11b/g)	
	WPS: support PIN and PBC	
	SSID broadcast control	
Output Power	802.11b: 18dBm (typical)	
	802.11g: 15dBm (typical)	
	802.11n (draft) : 7dBm (typical) with HT20 & HT40	
Receiving Sensitivity	802.11b: -86dBm (typical) @ 11Mbps	
	802.11g: -74dBm (typical) @ 54Mbps	
	802.11n (draft) : -70dBm (typical) with HT40	
Channels	• 1~11 (US), 1~13 (EU)	

NETWORKING SOLUTIONS



PACKAGE CONTENTS

- TEW-631BRP
- · Multi-Language Quick Installation Guide
- Easy-Go installation CD-ROM
- Power Adapter (12V DC, 1A)
- RJ-45 Cable (1.5m)

RELATED PRODUCTS

TEW-621PC	Wireless N PC Card
TEW-623PI	Wireless N PCI Adapter
TEW-630APB	300Mbps Wireless N Access Point
TEW-624UB	300Mbps Wireless N USB 2.0 Adapter

ORDERING INFORMATION

TRENDOET

20675 Manhattan Place, Torrance, CA 90501 USA

Tel: 1-310-961-5500 Fax: 1-310-961-5511 Web: www.trendnet.com Email: sales@trendnet.com

To Order Please Call:

1-888-326-6061

