



TK-400K **4-Port KVM Switch Kit**

TRENDnet's TK-400K 4-Port KVM Switch kit allows you to manage multiple PC's with just one keyboard, monitor, and mouse. Switch between PC's with a simple press of a button! Eliminate the hassle of cable swapping and save space with TRENDnet's TK-400K. It lets you control up to four PC's while using a single keyboard, monitor, and mouse. And with its Hot-Plug, Auto-Scan, Audible Feedback, and Hot-Key Operation features, TRENDnet's TK-400K is the perfect choice for managing multiple PC's.



FEATURES

- Use one keyboard, monitor, and mouse to control four computers
- PS/2 Keyboard/Mouse emulation
- 4-Port KVM switch in palm size design
- Includes four KVM cables (1.8 meters/ 6 feet)
- Support Microsoft Intellimouse, Logitech Net Mouse, Optical Mouse...etc.
- Support DOS, Windows 3.x/95/98/ME/NT/2000/XP, Netware, Unix, Linux, and more
- Hot-Plug feature, add PC's or remove connected PC's for maintenance without powering down the KVM switch or other PC's.
- Support very High Video Quality, up to 1920 x 1440 with 200Mhz bandwidth
- No software required, easy PC selection via Push Button and Hot-Keys
- Auto-Scan Mode for monitoring PC's.
- Keyboard status restored when switching between PC's.
- LED display for easy status monitoring
- Beeping sound for port switching confirmation
- 1-Year Warranty

BENEFITS

- **Integration Friendly:**
Does not require driver/software for the installation and operation. Switching between PC's with the push button or Hot-Key operation.
- **Flexible:**
Hot-Plug feature, add PC's or remove connected PC's without powering off the KVM Switch or the other PC's.
- **Cost Effective:**
Manage up to four PC's with single keyboard, monitor, and mouse. Save on equipment cost, utility, and space.
- **Performance:**
Support very High Video Quality up to 1920 x 1440 with 200Mhz bandwidth. Keyboard status is saved for each PC.



TK-400K

4-Port KVM Switch Kit

SPECIFICATIONS

Computer Connections:

- 4

Port Connectors:

- Keyboard & Mouse: PS/2 type 6-pin mini Din. Monitor: 15-pin HDDB type

KVM Cable:

- 4 sets of high-grade KVM cables (UL2919 for VGA monitor).

Length:

- 1.8 meters (6 feet)

Console Port:

- 1

Port Selection:

- Push Button and Hot-Keys

Auto-Scan Intervals:

- 4 seconds

Switching Confirmation:

- Beeping sound

Keyboard State:

- Saved and restored

Power Supply:

- Draw power from computer's keyboard port.
- Optional external power supply (for battery powered PC): 5V~9V DC, 500mA~1A (connector jack center positive)

Dimensions:

- 192 x 81 x 31 mm (1.56 x 3.19 x 1.22 inches)

Weight:

- Appro. 240 g. (8.5 Oz.)

Temperature:

- Operating: 0° ~ 40°C (32° ~ 104°F)
- Storage: -20° ~ 60°C (-4° ~ 140°F)

Humidity:


- 0%~80%, Non-Condensing

Certifications:

- FCC, CE



NETWORKING SOLUTIONS



To Order Please Call:
1-888-326-6061

PRODUCT INFORMATION

- TK-200K: 2-Port KVM Switch Kit
- TK-205i: 2-Port KVM Switch with Integrated Cables
- TK-400K: 4-Port KVM Switch
- TK-401R: 4-Port Rack-Mountable KVM Switch
- TK-800R: 8-Port KVM Stackable Rack-Mountable Switch (with OSD)
- TK-801R: 8-Port Rack-Mountable KVM Switch

ORDERING INFORMATION

TRENDware International, Inc.
3135 Kashiwa Street
Torrance, CA. 90505. USA
Tel: 310-891-1100
Fax: 310-891-1111
Web: www.TRENDNET.com
Email: sales@trendware.com

TRENDnet
TRENDware, USA