






## SFP Multi-Mode LC Module (550m)

TEG-MGBSX (4.0R)

- Transmission distance of up to 550m (1804 ft.)
- Supports data rates of up to 1.25Gbps
- Compliant with IEEE 802.3z Gigabit Ethernet
- ANSI Fiber Channel compliant
- Small Form-Factor Pluggable (SFP) and Multi-Source Agreement (MSA) compliant
- Low Electromagnetic Interference (EMI) design
- Supports 850nm multi-mode network transmissions
- Duplex LC optical interface
- Low power consumption
- Lifetime Warranty

TRENDnet's SFP Multi-Mode LC Module, model TEG-MGBSX, are compatible with standard SFP slots found on network switches and fiber media converters. The Multi-Mode SFP LC module is equipped with a duplex LC fiber connection interface, and supports gigabit multi-mode fiber connections for long distance networking applications.



### Fiber Applications

Long distance fiber networking for manufacturing, business parks, and school campus applications.

### Fiber Mode/Distance

Multi-Mode transceiver spans distances up to 550m (1804 ft.) at gigabit speeds.

### Compatibility

Hot-pluggable with an MSA compliant SFP slot, and compatible with fiber cables with LC-type duplex connectors.

## NETWORKING SOLUTION

LC duplex connector



SFP MSA Compliant



## FEATURES



### Hot-Pluggable SFP

Hot-pluggable SFP LC transceiver compatible with an MSA compliant SFP slot



### Fiber Wavelength

Compatible with multi-mode 850nm transmissions



### Fiber Distance

The multi-mode SFP supports networking for distances up to 550m (1804 ft.)



### Fiber Interface

SFP duplex LC connector

## SPECIFICATIONS

### Standards

- IEEE 802.3
- IEEE 802.3u
- IEEE 802.3z

### Device Interface

- SFP MSA Compliant
- LC duplex connector

### Data Transfer Rate

- 1.25Gbps

### Wavelength

- 850nm

### Optical Output Power

- -9 ~ -3 dBm

### Distance

- 550m (1804 ft.)

### Special Features

- Hot pluggable
- Metal enclosure

### Sensitivity

- -20 dBm

### Power

- Max. Consumption: 0.8W

### Operating Temperature

- 0° – 70° C (32° – 158 °F)

### Operating Humidity

- Max. 85% non-condensing

### Dimensions

- 57 x 13 x 12 mm (2.2 x 0.5 x 0.5 in.)

### Weight

- 18g (0.6 oz.)

### Certifications

- CE
- FCC

### Warranty

- Lifetime

### Package Contents

- TEG-MGBSX
- Quick Installation Guide

TRENDnet offers a lifetime warranty on selected fiber networking products that have been purchased in the United States/Canada on or after 1/1/2019.

All references to speed are for comparison purposes only. Product specifications, size, and shape are subject to change without notice, and actual product appearance may differ from that depicted herein.