




## 8-Port Unmanaged 2.5G Switch

TEG-S380 (v1.1R)


- 8 x 2.5GBASE-T ports
- IEEE 802.3bz (2.5G) compliant
- Backwards compatible with 10/100/1000Mbps devices
- 40Gbps switching capacity
- Fanless design eliminates noise
- Wall mountable for installation flexibility
- NDAA / TAA compliant (U.S. and Canada only)

Expand your network's bandwidth and reduce digital bottlenecks with TRENDnet's Unmanaged 2.5G Switches. These 2.5G network switches come equipped with 2.5GBASE-T RJ-45 ports that provide higher gigabit speeds capable of up to 2.5Gbps over your existing Cat5e or better cabling. Each high-speed 2.5G switch features a durable metal enclosure and can be mounted to the wall for setup flexibility. The fanless design lowers energy consumption and eliminates distracting operating noise. TRENDnet's reliable 2.5G switches are cost-effective solutions to increase your network's throughput.




### 2.5G Ports

Equipped with 2.5GBASE-T RJ-45 ports that provide higher gigabit speeds capable of up to 2.5Gbps over existing Cat5e or better cabling.



### Wall Mountable


The 2.5G switches feature metal housing with a convenient wall mountable design for greater installation flexibility.




### Fanless


The fanless design of the 2.5G switches lowers energy consumption costs and eliminates operating noise.


## NETWORKING SOLUTION





## FEATURES


- 


**Easy Installation**  
No configuration needed, simply connect network devices to the 2.5G Ethernet switch
- 

**2.5G Ports**  
Equipped with 2.5GBASE-T RJ-45 ports that provide higher gigabit speeds capable of up to 2.5Gbps over existing Cat5e or better cabling
- 


**Fanless**  
Fanless design lowers energy consumption and eliminates operating noise
- 

**Housing Design**  
Sturdy metal housing
- 

**Wall Mountable**  
Features a convenient wall mountable design for greater installation flexibility
- 

**Jumbo Frame**  
Sends larger packets, or Jumbo Frames (up to 12KB) for increased performance
- 

**LED Indicators**  
LED indicators on this 2.5G switch conveys port status



## SPECIFICATIONS

### Standards

- IEEE 802.3x
- IEEE 802.3z
- IEEE 802.3ab
- IEEE 802.3az
- IEEE 802.3bz

### Device Interface

- 8 x 2.5GBASE-T ports (1Gbps/ 2.5Gbps)
- LED indicators

### Data Transfer Rate

- Gigabit: 2000Mbps (full duplex)
- 2.5 Gigabit: 5Gbps (full duplex)

### Performance

- Switching Capacity: 40Gbps
- RAM Buffer: 1.5MB
- MAC Address Table: 16K entries
- Forwarding Rate: 29.76Mpps (64-byte packet size)
- Jumbo Frames: 12KB

### Special Features

- Wall-Mountable

### Power

- Input: 100 – 240V AC, 50/60 Hz, 0.6A
- Output: 12V DC, 1.5A
- Max. Consumption: 12.4W

### Fan/Acoustics

- Fanless design

### MTBF

- 1,401,356 hours

### Operating Temperature

- 0° – 40° C (32° – 104° F)

### Operating Humidity

- Max. 90% non-condensing

### Dimensions (L x W x H)

- 240 x 103 x 26mm (9.4 x 4.0 x 1.02 in.)

### Weight

- 600g (1.32 lbs.)

### Certifications

- FCC
- CE

### Warranty

- 3 year

### Package Contents

- TEG-S380
- Quick Installation Guide
- Power adapter (12V DC, 1.5A)

All references to speed are for comparison purposes only. Product specifications, size, and shape are subject to change without notice, and actual product appearance may differ from that depicted herein.