



TEW-501PC 108Mbps 802.11a/g Wireless CardBus PC Card

TRENDnet's TEW-501PC 802.11a/g Wireless PC card is a flexible and affordable wireless solution that allows your mobile workstation to connect to three wireless networks: 802.11a, 802.11g, or 802.11b. The TEW-501PC can operate at a blazing 108Mbps. For wireless security, the TEW-501PC uses WPA-PSK with AES and TKIP encryption algorithms and WEP.




FEATURES

- Wi-Fi Compliant with IEEE 802.11a, 802.11g and IEEE 802.11b Standards
- Uses 5 GHz or 2.4 GHz Dual Band Design, which Complies with Worldwide Requirements
- Supports Ad-Hoc (Peer-to-Peer) Mode or Infrastructure (AP-Client) Mode
- Supports Super AG technology Data Rate up to 108Mbps
- Dynamic Data Rate Scaling at 54, 48, 36, 24, 18, 12, 9 and 6Mbps for 802.11a/g
- Dynamic Data Rate Scaling at 11, 5.5, 2 and 1Mbps for 802.11b
- Maximum Reliability, Throughput and Connectivity with Automatic Data Rate Switching
- Compatible with Windows 98se/ME/2000/XP (SP1/SP2)/2003 Server
- Supports 64/128/152-bit WEP, WPA (AES/TKIP)
- Supports Wireless Multimedia Enhancements Quality of Server (QoS IEEE 802.11e draft)
- Integrated PCB Antenna for the Multi-Path Environment
- Low Interference and High Susceptibility Guarantee Reliable Performance
- Range of 35~100 meters indoor, 100~300 meters outdoor (depends on the environment)
- Simple User Setup & Diagnostics Utilities
- 3-Year Warranty

BENEFITS

- **Economical:**
Save Time, Labor, and Materials;
Compare with Wired Network Installation
- **Flexible:**
Creates wireless peer-to-peer network in Ad-Hoc mode or connects to Ethernet LAN in Infrastructure mode using Wireless Access Point or Wireless Router
- **Cost Effective:**
Supports IEEE 802.11a, IEEE 802.11b and IEEE 802.11g Standards;
Connects to any IEEE 802.11a and 802.11b/g wireless network
- **Performance:**
108Mbps High Speed Wireless Connection



TEW-501PC

108Mbps 802.11a/g Wireless CardBus PC Card

SPECIFICATIONS

Hardware

Interface:

- 32-Bit 3.3V CardBus Type II Card

Standards:

- IEEE 802.11a, IEEE802.11b and IEEE 802.11g

Antenna:

- PCB Antenna

LED Indicator:

- Power, Link

Power Consumption:

- 11a 54Mbps - Receive Mode: 270mA
- Transmit Mode: 380 mA

Support OS:

- Windows 98SE/ME/2000/XP(SP1/SP2), 2003 Server

Dimensions (LxWxH):

- 114 x 54 x 7mm (4.5 x 2.1 x 0.2 inches)

Weight:

- 36g (1.27oz)

Temperature:

- Operating: 0° ~ 50° C (32° ~ 104° F)
- Storage: -25° ~ 70° C (-4° ~ 158° F)

Humidity:

- 10% ~ 90% max. (Non-condensing)

Certification:

- FCC, CE



Wireless

Module Technique:

- 802.11b: CCK (11 and 5.5Mbps), DQPSK (2Mbps), DBPSK (1Mbps)
- 802.11a/g: OFDM with BPSK, QPSK and 16/64-QAM Sub-Carrier Modulations

Frequency:

- 802.11a: UNI-Band 5.15 ~ 5.85 Ghz
- 802.11 b/g: ISM 2.412 ~ 2.484Ghz

Media Access Protocol:

- CSMA/CA

Encryption:

- 64/128/152-Bit WEP (Hex or ASCII), WPA (AES/TKIP)

Data Rate (auto fallback):

- 802.11b: 11Mbps, 5.5Mbps, 2Mbps, and 1Mbps
- 802.11a/g: 54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 9Mbps and 6Mbps
- Super AG: 108Mbps

Transmit Power:

- 802.11a: 14dBm (typically)
- 802.11b: 19dBm (typically)
- 802.11g: 16dBm (typically)


Receiving Sensitivity:

- 802.11a: 11Mbps 10 – 5 BER @ -71 dBm (typical)
- 802.11b: 11Mbps 10 – 5 BER @ -84 dBm (typical)
- 802.11a/g: 54Mbps 10 – 5 BER @ -71 dBm (typical)

Channels:

- 2.4GHz : 1~11 (US), 1~13 (EU)
- 5GHz : Country dependence

NETWORKING SOLUTIONS



To Order Please Call:
1-888-326-6061

RELATED PRODUCT

- > **TEW-503PI**
108Mbps 802.11a/g Wireless PCI Adapter
- > **TEW-504UB**
108Mbps 802.11a/g Wireless USB 2.0 Adapter
- > **TEW-510APB**
108Mbps 802.11a/g Wireless Access Point

ORDERING INFORMATION

TRENDware International, Inc.
3135 Kashiwa Street
Torrance, CA. 90505. USA
Tel: 310-891-1100
Fax: 310-891-1111
Web: www.TRENDNET.com
Email: sales@trendware.com

TRENDnet
TRENDware, USA