







300 Mbps Wireless N Gigabit Router TEW-633GR (V1.1)

The 300Mbps Wireless N Gigabit Gaming Router incorporates the latest wireless and Gigabit networking technology to increase speed, range, security and reliability. The router provides unsurpassed gaming and network experience and performance.

Advanced antenna and 802.11 N technology increases wireless data range and coverage. Enjoy lag-free gaming and file transfers on your wired Gigabit computers via the built-in Gigabit switch. This router features a powerful firewall and advanced wireless encryption for secured transmissions. Quality of Service (QoS) prioritization provides a seamless gaming and multimedia streaming experience. Increased speed, throughput and range make it the perfect solution to fulfill your gaming needs.

** Maximum wireless signal rates are referenced from IEEE 802.11 theoretical specifications. Actual data throughput and coverage will cary depending on interference, network traffic, building materials and other conditions.

FEATURES

- Wi-Fi compliant with IEEE 802.11n and IEEE 802.11b/g standards
- 4 x 10/100/1000Mbps Auto-MDIX Gigabit LAN port and 1 x 10/100/1000Mbps Gigabit WAN port (Internet)
- Supports Cable/DSL modems with Dynamic IP, Static IP, PPPoE, PPTP, L2TP & BigPond connection types
- High-speed up to 300Mbps data rate using IEEE 802.11n connection
- Built-in 3 external antennas support high speed performance and great coverage
- Firewall features Network Address Translation (NAT), and Stateful Packet Inspection (SPI) protects against DoS attacks
- Traffic control with virtual servers, special applications, gaming services & Ubicom StreamEngine™ feature
- UPnP (Universal Plug & Play) and ALGs support for internet applications such as email, FTP, gaming, remote desktop, Net Meeting, telnet, and more
- Provides additional security of enable/disable wireless SSID, internet access control (services, URL & MAC filtering)
- Supports multiple and concurrent IPSec, L2TP and PPTP VPN pass-through sessions
- Supports Static Routing RIPv1 announcer
- · Easy management via web browser (IE 6.0 or above, Firefox, Opera, Netscape) and remote management
- Supports 64/128-bit WEP(for 11b/g), WPA/WPA2 and WPA-PSK/WPA2-PSK
- Compliant with Windows 95/98/NT/2000/XP/2003 server/Vista, Linux and Mac OS
- Coverage up to 150 meters (500ft.) indoor(depends on the environment)
- Coverage up to 400 meters (1300ft.) outdoor(depends on the environment)
- · 3 year warranty
- Link to Wi-Fi certification: http://certifications.wi-fi.org/wbcs ViewCertificate.php?product_id=5828

300 Mbps Wireless N Gigabit Router TEW-633GR

SPECIFICATIONS


Hardware		
Standards	Wired: IEEE 802.3 (10Base-T), IEEE 802.3u (100Base-TX), IEEE 802.3ab (1000Base-T)	
	 Wireless: IEEE 802.11b, IEEE 802.11g, IEEE 802.11n (draft 2.0), IEEE 802.11e QoS 	
WAN	1 x 10/100/1000Mbps Auto-MDIX gigabit port (Internet)	
LAN	4 x 10/100/1000Mbps Auto-MDIX gigabit port	
Slide Switch	Turn On/Off Wireless LAN	
WPS Button	Enable WPS function (PIN setup)	
Connection Type	Dynamic IP, Static (Fixed) IP, PPPoE, PPTP, L2TP, BigPond	
NAT Firewall	3K configurable NAT entries; Restricted NAPT	
	IP Ranges, Port Ranges & Schedule	
	Pre-Defined Game Hosting Configurations	
	Port triggering for 24 special applications	
	 ALG support (enable/disable support) – PPTP, IPSec, RTP/RTSP, AOL, FTP, ICMP, WMP/MMS, NetMeeting, SIP, MSN Messenger, Wake on LAN 	
	UP to 24 Rules	
SPI Firewall	Cyber Attack Protection – Verified Against Over 2000 Attacks	
Multicast Stream	Enable/Disable control support	
UPnP	UPnP IGD Compliant	
DMZ	DMZ Host, 24 Configurable Virtual Servers & Game Servers	
DNS	Static or WAN assigned DNS Servers	
	10 verified services for DDNS	
Internet Access Control	 Policy based parental control; Time based internet access; Port range/service filtering; Dynamic URL filtering; Internet domain restriction; 32 user defined schedules, 24 MAC Address Filter Entries 	
Logging	3 types & 3 severities event logging; up to 1K entries	
	Email report logging on schedule or log full	
LED Indicator	• Power, LAN1~LAN4, WAN, WLAN	
Power Adapter	12V DC, 1A External Power Adapter	
Power Consumption	• 779mA	
Dimensions (LxWxH)	• 150 x 162 x 25 mm (5.9 x 6.4 x 1 inches)	
Weight	• 335g (11.8oz)	
Temperature	• Operating: 0° ~ 40° C (32° ~ 104° F)	
	• Storage: -20° ~ 60° C (-4° ~ 140° F)	
Humidity	Max. 90% (Non-Condensing)	
Emissions	• CE, FCC	

300 Mbps Wireless N Gigabit Router TEW-633GR

SPECIFICATIONS

Wireless		
Frequency	• 2.412 ~ 2.462 GHz (FCC)	
	• 2.412 ~ 2.472 GHz (ETSI)	
Antenna	3 x 4dBi Fixed Dipole Antenna	
Media Access Protocol	CSMA/CA with ACK	
Data Rate (auto fallback)	802.11b: 11Mbps, 5.5Mbps, 2Mbps, and 1Mbps	
	 802.11g: 54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 9Mbps and 6Mbps 	
	802.11n (draft 2.0) : up to 300Mbps	
Security	Encryption: Hardware AES/TKIP, 64/128-bit WEP (Hex/Passpharse, for 11b/g)	
	802.1X/EAP: EAP-TLE,EAP-TTLE/MSCHAPv2, PEAPv0/EAP-MSCHAPv2, PEAPv1/EAP-GTC	
	WPA: WPA/WPA2, WPA-PSK/WPA2-PSK (AES-11b/g/n, TKIP-11b/g)	
	WPS: support PIN and PBC	
	SSID broadcast control	
Output Power	802.11b: 18dBm (typical)	
	802.11g: 15dBm (typical)	
	802.11n (draft 2.0): 6dBm (typical) with HT20 or HT40	
Receiving Sensitivity	802.11b: -84dBm (typical) @ 11Mbps	
	802.11g: -72dBm (typical) @ 54Mbps	
	802.11n (draft 2.0) : -70dBm (typical) with HT20 or HT40	
Channels	• 1~11 (US), 1~13 (EU)	

NETWORKING SOLUTIONS



PACKAGE CONTENTS

- TEW-633GR
- Multi-language quick installation guide
- · Easy-Go installation CD-ROM
- Power Adapter (12V DC, 1A)
- RJ-45 Cable (1.5m)

RELATED PRODUCTS

TEW-621PC	300Mbps Wireless N-Draft PC Card
TEW-623PI	300Mbps Wireless N-Draft PCI Adapter
TEW-624UB	300Mbps Wireless N USB 2.0 Adapter
TEW-630APB	300Mbps Wireless N-Draft Access Point

ORDERING INFORMATION

TRENDNET[®]

20675 Manhattan Place, Torrance, CA 90501 USA

Tel: 1-310-961-5500 Fax: 1-310-961-5511 Web: <u>www.trendnet.com</u> Email: sales@trendnet.com

To Order Please Call:

1-888-326-6061

