



## AC1200 High Gain Dual Band Wireless USB Adapter

TEW-805UBH (v1.0R)


- Quick and easy setup
- Adjustable High-Gain external antenna
- High speed WiFi AC1200 Wave 2 MU-MIMO adapter
- Selectable WiFi AC (867Mbps) or WiFi N (300Mbps) radios
- Dual band support for 2.4GHz and 5GHz WiFi networks
- Physical WPS button for ease of connectivity
- Upgrade your laptop or desktop to wireless AC
- WMM Quality of Service (QoS) data prioritization
- Supports Windows® and Mac® operating systems
- LED-Indicators

TRENDnet's AC1200 High Gain Dual Band Wireless USB Adapter, model TEW-805UBH, connects a laptop or desktop computer to a high-speed WiFi AC867 or WiFi N300 network. Seamlessly stream video, download files, and play games with this Wave 2 MU-MIMO wireless AC adapter. Wi-Fi Multimedia Quality of Service prioritizes important video, audio, and gaming traffic. This adapter features an adjustable high gain antenna which increases wireless coverage and performance.




## AC1200 WiFi

Connects a laptop or desktop computer to a high-speed WiFi AC867 or WiFi N300 network.



## High Gain Antenna

Adjustable high gain antenna increases wireless coverage and performance.



## Wave 2 MU-MIMO

Seamlessly stream video, download files, and play games with this Wave 2 MU-MIMO wireless AC adapter.

## NETWORKING SOLUTION



## FEATURES



### Easy Setup

Get up and running in minutes with the intuitive guided setup



### AC1200 Wi-Fi

Connects a laptop or desktop computer to a high-speed Wi-Fi AC867 or Wi-Fi N300 network



### Wave 2 MU-MIMO

Seamlessly stream video, download files, and play games with this Wave 2 MU-MIMO wireless AC adapter.



### High Gain Antenna

Adjustable high gain antenna increases wireless coverage and performance



### Wireless Encryption

Supports up to WPA2 encryption



### Operating Systems

Compatible with Windows® and Mac® operating systems

## SPECIFICATIONS

### Standards

- IEEE 802.1x
- IEEE 802.11a
- IEEE 802.11b
- IEEE 802.11g
- IEEE 802.11n (up to 300Mbps)\*
- IEEE 802.11ac (up to 867Mbps)\*

### Hardware Interface

- USB 3.1 Gen 1
- LED Indicator
- WPS Button

### Special Features

- High-speed 802.11ac connectivity
- Explicit Beamforming
- Supports Wave 2 MU-MIMO technology

### Compatibility

- Windows® 10, 8.1, 8, 7
- Mac OS® 10.9 – 10.15
- Linux

### Data Rate

- 802.11a: up to 54Mbps
- 802.11b: up to 11Mbps
- 802.11g: up to 54Mbps
- 802.11n: up to 300Mbps (2.4GHz & 5GHz)
- 802.11ac: up to 867Mbps

### Encryption

- 64/128-bit WEP, WPA / WPA2-Enterprise, WPA / WPA2-PSK (AES/TKIP)

### Quality of Service

- WMM

### Frequency

- 2.400 – 2.4835GHz
- 5.150 – 5.825GHz

### Modulation

- 802.11b: CCK, DQPSK, DBPSK
- 802.11a/g: OFDM with BPSK, QPSK and 16/64-QAM
- 802.11n: BPSK, QPSK, 16-QAM, 64-QAM with OFDM
- 802.11ac: OFDM with BPSK, QPSK and 16/64/256-QAM

### Antenna

- 1 x dual-band Fixed Antenna, 2.4GHz: 2dBi (max) / 5GHz: 4dBi (max.)

### Output Power

- 802.11a: 9.5 dBm (max.) @ 54Mbps
- 802.11b: 12.5 dBm (max.) @ 11Mbps
- 802.11g: 10.5 dBm (max.) @ 54Mbps
- 802.11n (2.4GHz): 9.5 dBm (max.) @ 300Mbps
- 802.11n (5GHz): 8.5 dBm (max.) @ 300Mbps
- 802.11ac: 6.5 dBm (max.) @ 867Mbps

### Receiving Sensitivity

- 802.11a: -70 dBm (typical) @ 54Mbps
- 802.11b: -82 dBm (typical) @ 11Mbps
- 802.11g: -70 dBm (typical) @ 54Mbps
- 802.11n (2.4GHz): -67 dBm (typical) @ 300Mbps
- 802.11n (5GHz): -64 dBm (typical) @ 300Mbps
- 802.11ac: -54 dBm (typical) @ 867Mbps

### Wireless Channels

- 2.4GHz: FCC: 1-11; ETSI: 1-13
- 5GHz: FCC: 36, 40, 44, 48, 149, 153, 157, 161, 165; ETSI: 36, 40, 44, 48, (52, 56, 60, 64, 100, 104, 108, 112, 116, 132, 136, 140)\*\*

### Power

- Consumption: Max. 2.26W

### Operating Temperature

- 0° – 40° C (32° – 104° F)

### Operating Humidity

- Max. 90% non-condensing

### Dimensions (L x W x H)

- 175 x 17.5 x 17.5 mm (6.9 x 0.7 x 0.7 in.)

### Weight

- 16g (0.5 oz.)

### Certifications

- CE
- FCC

### Warranty

- 3 year

### Package Contents

- TEW-805UBH
- CD-ROM (Driver & User's Guide)
- Quick Installation Guide

\*Maximum wireless signal rates are referenced from IEEE 802.11 theoretical specifications. Actual data throughput and coverage will vary depending on interference, network traffic, building materials, and other conditions. For maximum performance of up to 867Mbps, use with an 867Mbps 802.11ac wireless Access Point. For maximum performance of up to 300Mbps, use with a 300Mbps 802.11n wireless Access Point. Multi-User MIMO (MU-MIMO) requires the use of multiple MU-MIMO enabled wireless adapters and Access Points.

\*\*Due to regulatory requirements, the wireless channels specified cannot be statically assigned, but will be available within the available wireless channels when set to auto.

All references to speed are for comparison purposes only. Product specifications, size, and shape are subject to change without notice, and actual product appearance may differ from that depicted herein.

20675 Manhattan Place • Torrance • CA 90501 • USA • T: 1-888-326-6061 • F: 1-310-961-5511 • [intlsales@trendnet.com](mailto:intlsales@trendnet.com) • [www.TRENDnet.com](http://www.TRENDnet.com)

TRENDnet is a registered trademark. Other Brands and product names are trademarks of their respective holders. Information provided in this document pertain to TRENDnet products and is subject to change at any time, without notice. For the most recent product information please visit <http://www.trendnet.com>. Copyright © TRENDnet. All Rights Reserved.

Updated: 4/6/2021