



AC600 High Gain Dual Band Wireless USB Adapter TEW-806UBH (v1.0R)

- · High gain antenna increases wireless coverage
- Upgrade your computer to 433 Mbps Wireless AC
- Connect to a Wireless N network at up to 150 Mbps
- Quick intuitive setup
- Powered by the computer's USB port
- Windows® and Mac® compatible

TRENDnet's AC600 High Gain Dual Band Wireless USB Adapter, model TEW-806UBH, connects a Windows® or Mac® computer to a revolutionary Wireless AC network. Connect to a Wireless AC network at 433 Mbps or to a Wireless N network at up to 150 Mbps. This adapter features an adjustable high gain antenna which significantly increases wireless coverage.



Ease of Use



Easy Setup

Get up and running in minutes with the intuitive guided setup



Operating Systems

Compatible with Windows® and Mac® operating systems



One Touch Connection

Securely connect to the router at the touch of the Wi-Fi Protected Setup (WPS) button

Performance



High Gain Antenna

An adjustable high gain antenna significantly increases wireless coverage



Next Generation Wireless AC

802.11ac provides uninterrupted HD video streaming in a busy connected home



Dual Band

High speed 433 Mbps Wireless AC + 150 Mbps Wireless N bands



Encrypted Wireless

Supports the latest encryptions standards (up to WPA2)



Backward Compatible

Compatible with legacy wireless devices

Networking Solution



























Specifications

Standards

- IEEE 802.11a
- IEEE 802.11b
- IEEE 802.11g
- IEEE 802.11n (up to 150 Mbps)
- IEEE 802.11ac (draft 2.0, up to 433 Mbps)

Hardware Interface

- USB 2.0
- WPS Button
- · LED indicator
- · Adjustable antenna

Encryption

• Wireless encryption up to WPA2

Compatibility

- Windows® 8.1, 8, 7, Vista, XP
- Mac OS® 10.6 10.9

Special Features

 High gain 5 dBi antenna for long distance networking (5 GHz band)

* For maximum performance connect to an 802.11ac wireless router or access point.

interference, network traffic, building materials and other conditions.

- · Adjustable antenna
- High-speed 802.11ac connectivity

Power

· Consumption: Max. 300 mA

Operating Temperature

• 0 - 40 °C (32 - 104 °F)

Operating Humidity

• Max. 90% non-condensing

Certifications

- CE
- FCC

Dimensions

• 188 x 17 x 18 mm (7.4 x 0.7 x 0.7 in.)

** Maximum wireless signal rates are referenced from IEEE 802.11 theoretical specifications. Actual data throughput and coverage will vary depending on

Weight

• 17 g (0.6 oz.)

Warranty

• 3 year limited

Package Contents

- TEW-806UBH
- · Multi-Language Quick Installation Guide
- CD-ROM (Utility & Drivers)

