

Firmware Upgrade Procedure

1. Save the downloaded firmware file (.zip) to your PC
2. Right click on the downloaded file and select **Extract All** or **Extract Here** option
 - a. Make sure to remember the location where the extracted file will be saved.
3. Log into to the router's configuration page (default IP address <http://192.168.10.1>)
4. Navigate to the **Tools** section and click on **Firmware Upgrade**.

Firmware Upgrade - Upload

To upload a firmware image for upgrading your mesh devices.

Firmware image:

Choose File

No file chosen

Upload

5. Click **Browse** (or **Choose File**) and select the firmware file (.bin) from the extracted files and click the **Upload** button to start the firmware upgrade process. When prompted to upgrade multiple TEW-830MDR units. If prompted, click **Start** to upgrade all TEW-830MDR units detected in your mesh network. If not prompted, multiple TEW-830MDR units can also be upgraded using the online upgrade feature in the TRENDnet Mesh app.

Firmware Upgrade - Verify

The firmware image is ready for upgrade. Below is its file size and checksum listed, compare them with the original file to ensure data integrity.

Press "Start" button to start the process.

- Model Name: **TEW-830MDR**
- Size: **23.00 MB**
- Checksum: **794ccb59520befc8adf88e8877657bca**

Mesh Device List

Model	Location	MAC Address	Current Version	Status
TEW-830MDR	TRENDnet459681	88:DC:96:6D:A0:FC	v1.0.15	Waiting.....
TEW-830MDR	Living Room	88:DC:96:6D:A1:00	v1.0.15	Firmware Downloaded

Cancel

Start

6. Wait until the firmware upload has completed and the device(s) reboots.
7. The firmware upgrade is complete.