



Intelligent 1000Base-T to 1000Base-LX Single-Mode SC Fiber Converter (50km/31miles)

TFC-1000S50 (C1.0R)

- SC-type single-mode fiber port connects over distances of up to 50km (31 miles)
- 1000Base-T Gigabit copper port supports Full-Duplex mode
- Supports port level SNMP management
- Functions as a stand alone converter or with the TFC-1600 fiber chassis
- Lifetime Warranty

The TFC-1000S50 Intelligent Fiber Converter works with the TFC-1600 chassis system or as a standalone unit. This converter is a Single Mode SC-Type fiber converter that supports SNMP and spans distances up to 50km (31miles). Ports include 1 x 1000Base-T (RJ-45) port and 1 x 1000Base-LX (SC-Type) port.

- Compliant with IEEE 802.3ab 1000Base-T and IEEE 802.3z 1000Base-LX standards
- 1 x 1000Base-T RJ-45 port
- 1 x 1000Base-LX single-mode SC type fiber port
- Provides Dip switch to set: Fiber (Forced/Auto-Negotiation), LLR (Enable/Disable)
- Support LLCF (Link Loss Carry Forward, Link Pass Through)
- Support LLR (link Loss Return) for Fiber port
- Monitor and configure Ethernet or Fiber's duplex mode, LLR, port on/off and receive link down information via management module TFC-1600MM and chassis TFC-1600
- Status LED indicators for Power and Link/Activity
- Wall mountable
- Optional 19" system chassis with redundant power supply (TFC-1600), holds up to 16 TFC series Media Converters
- Lifetime Warranty

Specifications

Hardware

Standard

- IEEE802.3ab 1000Base-T, IEEE 802.3z 1000Base-LX

Supported Frame Size

- Standard Ethernet up to 10Kbytes

Network Media

- 1000Base-T : Cat. 6 EIA/TIA-568 100-ohm UPT/STP, up to 100m 1000Base-LX : Single-mode fiber optic cable 9/125 μm or 10/125 μm , up to 50km

Protocol

- CSMA/CD

Ports

- 1 x 1000Base-T 1 x 1000Base-LX (SC-type)

Dip Switch

- Fiber (forced/auto-negotiation), LLR (enable/disable)

Transfer Rate

- 2000Mbps (full-duplex)

Diagnostic LED

- Per Unit : power
- Per Port : link/activity

Power Adapter

- 7.5V DC, 1A external power adapter

Power Consumption

- 2.7 Watts (max)

Dimensions

- 120 x 88 x 25mm (4.7 x 3.46 x 0.98 in.)

Weight

- 354g (12.5oz)

Temperature

- Operating : 0° ~ 40° C (32° ~ 104° F)
- Storage : -25° ~ 70° C (-13° ~ 158° F)

Humidity

- Max. 90% (non-condensing)

Certification

- CE, FCC

Media

- SMF

Wavelength

- 1550nm

Pout (dBm)

- -4 ~ +1

Sensitivity

- -23 ~ -3

Power

- 19

Distance

- 50km

Package Contents

- TFC-1000S50
- Multi-Language Quick Installation Guide
- Power Adapter (7.5V, 1A)

TRENDnet offers a limited lifetime warranty on selected fiber networking products that have been purchased in the United States/Canada on or after 1/1/2019.