



10/100Mbps-TX to 100Base-FX Dual-Wavelength Single-Mode Fiber Converter TFC-210S20D3 (v1.0R)

TFC-210S20D3 Bi-Directional Single-Fiber Media Converter transforms 10/100Mbps-TX UTP/STP media to 100Base-FX media and vice versa. The 10/100Mbps-TX Port Auto-Negotiating 10 or 100Mbps connection speed with Auto-MDIX media type, the fiber supports single-mode SC type connection. This converter will give your Switch/Hub the ability to interface with fiber connection over a distance up to 20 km.

FEATURES

- Compliant with IEEE 802.3 10Base-T and IEEE 802.3u 100Base-TX, 100Base-FX standards
- One 10/100Base-TX Auto-Negotiation/Auto-MDIX RJ-45 port
- One 100Base-FX Dual-Wavelength Single-Mode Single-Strand SC-type Fiber port
- Supports LLCF (Link Loss Carry Forward)
- Provides Dip switch to set: UTP (Auto Negotiation/Full Duplex), Fiber (Half Duplex/Full Duplex), LLCF (Enable/Disable), Mode (Pure Converter Mode/ Switch Converter Mode)
- 802.3x flow control for 10/100Base-TX port
- Plug & Play, Hot Pluggable
- Diagnostic LEDs
- Optional 19" Fiber Converter Chassis (TFC-1000) holds up to 10 Fiber Converters
- 5-Year Warranty

10/100Mbps-TX to 100Base-FX Dual-Wavelength Single-Mode Fiber Converter TFC-210S20D3 (v1.0R)

SPECIFICATIONS

Hardware	
Standard	• IEEE 802.3 10Base-T • IEEE 802.3u 100Base-TX, 100Base-FX
Network Media	• 10Base-T: UTP/STP Cat. 3, 4, 5, EIA/TIA-568 100-ohm • 100Base-TX: UTP/STP Cat. 5, EIA/TIA-568 100-ohm • 100Base-FX: 9/125um Single Mode Simplex SC-Type Cable, up to 20km
Minimum Cable Length	• 50 Meters
Protocol	• CSMA/CD
Frame Packet Size	• 64 to 1600 Bytes
Ports	• 1 x 10/100Base-TX RJ-45 Port • 1 x 100Base-FX Single-Mode Bi-Directional SC-Type Fiber Port
Dip Switch	• Dip Switch 1: ON: TX Port Fully Duplex OFF: TX Port Auto- Negotiation • Dip Switch 2: ON: FX Port Half Duplex OFF: FX Port Full Duplex • Dip Switch 3: ON: LLCF Enable OFF: LLCF Disable • Dip Switch 4: ON: Pure Converter Mode OFF: Switch Converter Mode * After changing the DIP Switch settings, power cycle the Fiber converter.
Transfer Rate	• 100Mbps (Half/Full Duplex)
Diagnostic LED	• Per Device: Power • Per port (TX): 100Mbps, Link/Activity, Full Duplex/Collision; (FX): Link/Activity, Full Duplex/Collision
Power Adapter	• 9V DC, 700mA External Power Adapter
Transfer Rate	• 3.1 Watts (max)
Dimensions	• 85 x 125 x 25mm (3.35 x 4.92 x 0.98in.)
Weight	• 300g (10.6oz.)
Temperature	• Operating : 0°C ~ 45°C (32°F ~ 113°F) • Storage : -40°C ~ 70°C (-40°F ~ 158°F)
Humidity	• 5% ~ 90% RH
Certification	• CE, FCC

	Media	Wavelength	Power Output (dBm)	Sensitivity	Power Budget (dBm)	Distance
TFC-210S20D3	WDM (Single Mode)	TX:1310nm (1260nm~1360nm) RX:1550nm (1480nm~1600nm)	-14	-31	17	20km

*The Single-Strand WDM Single-Mode Fiber Converter TFC-210S20D3 must be paired with TFC-210S20D5.

PACKAGE CONTENTS

- TFC-210S20D3
- Multi-Language Quick Installation Guide
- Power Adapter

RELATED PRODUCTS

TFC-1000	10-Bay Fiber Chassis
TFC-210S20D5	10/100Mbps-TX to 100Base-FX Dual-Wavelength Single-Mode Fiber Converter

ORDERING INFORMATION

TRENDnet®

20675 Manhattan Place, Torrance, CA 90501 USA
Tel: 1-310-961-5500
Fax: 1-310-961-5511
Web: www.trendnet.com
Email: sales@trendnet.com

To Order Please Call:

1-888-326-6061

