



16-Port Gigabit PoE+ Switch

TPE-TG160H (v1.0R)

- 16 x Gigabit PoE+ ports
- 32Gbps switching capacity
- 123W PoE power budget
- IEEE 802.3af/at compliant
- · Fanless design eliminates operating noise
- Reduces equipment cost by delivering data and power over existing network cables
- 1U 19" rack mountable with brackets included
- External power supply

Installers and integrators can save on equipment costs and reduce installation time with TRENDnet's Unmanaged Gigabit PoE+ Switches. The new fanless design reduces unnecessary energy consumption and eliminates disruptive operating noise. These fanless PoE+ switches deliver up to 30W per port of PoE power, and data over your existing Ethernet cables.

With PoE technology, users only need one set of cables to deliver both data and power. Connect and network your PoE and PoE+ devices, such as high-power wireless access points, PTZ and other advanced IP cameras, VoIP phone systems, IPTV decoders, and access controls, to reliable TRENDnet's fanless PoE+ switches.





PoE+

Features a 123W total PoE power budget, and supplies 16 Power over Ethernet devices with up to 30W per port.





Gigabit Ports

Equipped with high-speed gigabit ports and a full switching capacity, these PoE+ switches are well-suited for the most demanding network applications.

Fanless

Fanless PoE+ switch design lowers unnecessary energy consumption and eliminates disruptive operating noise.

NETWORKING SOLUTION





1U 19" rack mountable with brackets included

R TRENDNET

FEATURES



Easy Installation

No configuration needed, simply connect PoE+ network devices to the PoE+ switch



PoE+

Supplies up to 30W of power per port with data over a single Ethernet cable to PoE and PoE+ devices



Gigabit Ports

Equipped with high-speed gigabit ports and a full switching capacity, these fanless PoE+ switches are wellsuited for the most demanding networking applications

Jumbo Frame

Sends larger packets, or Jumbo Frames (up to 10KB) for increased performance



LED Indicators

LED indicators on the fanless PoE+ switches convey port status

SPECIFICATIONS

Standards

- IEEE 802.3
- IEEE 802.3u
- IEEE 802.3x
- IEEE 802.3ab
- IEEE 802.3af
- IEEE 802.3at

Device Interface

- 16 x Gigabit PoE+ ports
- LED indicators

Data Transfer Rate

- Ethernet: 10 Mbps (half duplex), 20 Mbps (full duplex)
- Fast Ethernet: 100 Mbps (half duplex), 200 Mbps (full duplex)
- Gigabit: 2000 Mbps (full duplex)

Performance

- Data RAM Buffer: 512KB
- Switch Fabric: 32Gbps
- MAC Address Table: 8K entries
- Forwarding rate: 23.8Mpps (64-byte packet size)
- Jumbo Frame: 10KB

Power

- Input: 100 240V AC, 50/60Hz, DC 54V/2.78A
- Max. consumption: 12.8W (no PD)

PoE

- PoE budget: 123W
- · PoE Mode A: Pins 1, 2, 3, and 6 for power
- · Over current protection
- Short circuit protection

MTBF

• 988,148 hours

Operating Temperature

• 0° - 45° C (32° - 104° F)

Operating Humidity

Max. 90% non-condensing

Dimensions

• 286 x 102 x 27mm (11.3 x 4 x 1 in.)

Weight

0.9kg (2 lbs.)

Certifications

- CE
- FCC

Warranty

3 year

Package Contents

- TPE-TG160H
- Quick Installation Guide
- · Rack mount kit
- Power Adapter (54V, 2.78A)

All references to speed are for comparison purposes only. Product specifications, size, and shape are subject to change without notice, and actual product appearance may differ from that depicted herein.

TRENDnet is a registered trademark. Other Brands and product names are trademarks of their respective holders. Information provided in this document pertain to TRENDnet products and is subject to change at any time, without notice. For the most recent product information please visit http://www.trendnet.com. Copyright © TRENDnet. All Rights Reserved.

included rackmount brackets, this PoE+ switch is well-suited for wall mount or 19" 1U rack installations

With a sturdy metal housing and

Housing Design

Fanless Fanless PoE+ switch design lowers energy consumption and eliminates operating noise

