



200Mbps Powerline AV Ethernet Adapter Kit TPL-302E2K (v1.0R)

The 200Mbps Powerline Ethernet Adapter Kit uses your existing electrical outlet to create a secure high speed building-wide network. Instantly network computers in different rooms without running new Ethernet cabling.

This adapter kit creates a stable high speed network and is ideal for use in building types that interfere with wireless networking signals. Advanced DES and 3DES encryption provides users with the latest Powerline data security. LED displays show device status for easy power management and troubleshooting. Connect one adapter to your network and plug the other adapter in to any electrical outlet in your building for instant high speed network access.

FEATURES

- Enjoy high speed building-wide networking over existing electrical lines
- Plug & Play support and Windows based configuration utility for a quick and simple installation
- Share data intensive files, play games, download music and more at very fast data transfer rates of up to 200Mbps
- Advanced encryption (AES) ensure total network security
- Connect one 200Mbps* Powerline AV Adapter to the Internet and then plug in up to 15 additional adapters for instant building connectivity
- Enjoy transmission distances of up to 300 meters (984ft.)
- Configuration utility compatible with Windows 2000/XP/Vista operating systems
- 3-year warranty

* 200Mbps is the maximum data rate possible. Actual throughput will vary depending on environment.

** Powerline AV adapters must be on the same circuit breaker/power phase.


200Mbps Powerline AV Ethernet Adapter Kit

TPL-302E2K (v1.0R)

SPECIFICATIONS

Hardware	
Standards	<ul style="list-style-type: none">• IEEE 802.3, IEEE 802.3u• HomePlug AV
Interface	<ul style="list-style-type: none">• 10/100Mbps Auto-MDIX RJ45 Port• Power Prongs
Frequency Band	<ul style="list-style-type: none">• 2 ~ 30 MHZ
Modulation	<ul style="list-style-type: none">• QAM, QPSK, BPSK, ROBO
Speed	<ul style="list-style-type: none">• Powerline: Up to 200Mbps• LAN: 10/100Mbps
Supported OS	<ul style="list-style-type: none">• Windows 2000/XP/Vista(32bit)
Nodes	<ul style="list-style-type: none">• Up to 16 client nodes
Encryption	<ul style="list-style-type: none">• 128-bit AES
LED	<ul style="list-style-type: none">• Power, Powerline, Ethernet
Dimension (L x W X H)	<ul style="list-style-type: none">• 78 x 30 x 102 mm (3 x 1.2 x 4 inches)
Weight	<ul style="list-style-type: none">• 140g (5 oz.)
Power Source	<ul style="list-style-type: none">• Input: 100~240V AC, 160mA
Consumption	<ul style="list-style-type: none">• 4.2 watts (max.)
Temperature	<ul style="list-style-type: none">• 0° ~ 40° C (32° ~ 104° F)
Humidity	<ul style="list-style-type: none">• 0% to 90% (Non-Condensing)
Certifications	<ul style="list-style-type: none">• FCC, CE

NETWORKING SOLUTIONS



PACKAGE CONTENTS

- TPL-302E x 2
- Multi-Language Quick Installation Guide
- Utility CD-ROM
- 1.8m (6ft) Cat.5 Fast Ethernet cable

ORDERING INFORMATION

TRENDnet®

20675 Manhattan Place, Torrance, CA 90501 USA

Tel: 1-310-961-5500

Fax: 1-310-961-5511

Web: www.trendnet.com

Email: sales@trendnet.com

To Order Please Call:

1-888-326-6061

