



USB to HDMI TV Adapter TU2-HDMI(V1.0R)

The USB to HDMI Monitor Extender, model TU2-HDMI, uses a USB port on your Windows-based computer to quickly add an HDMI monitor or television to your workstation.

Add an HDMI monitor or television to your computer by simply plugging in the TU2-HDMI—drivers will automatically install.

Features audio support for multiple audio protocols. Clone mode repeats a display area to the new HDMI based device. Extend mode stretches a display area over multiple monitors. Use up to six TU2-HDMIs to add six monitors or televisions to your workstation. Experience the visual impact of 32-bit True Color Depth technology and a sparkling 1920 x 1080 high definition image. Standard and wide screen viewing modes are supported.

FEATURES

- Compliant with monitors, televisions, and projectors with an HDMI port
- High definition of up to UXGA 1920 x 1080 resolution for standard or wide screen ratios
- Extend or mirror mode support
- Resumes from hibernation and standby modes
- Digital RGB, DAC, DVI, FPI display connectivity
- Supports four audio inputs: Dolby digital, DTS, DVD-Audio, and MPEG2
- 32-bit True Color Depth technology
- Supports Windows 8, 7, Vista, XP and Mac operating systems
- 2-year limited warranty

USB to HDMI TV Adapter

TU2-HDMI(V1.0R)

SPECIFICATIONS

HARDWARE

Standard	• USB 2.0
Interface	• HDMI 1.3 (up to 165MHz) – 19pin female connector • USB Mini-B type female connector
Power mode	• Bus-powered
Supported OS	• Windows 8 (32/64-bit), 7 (32/64-bit), Vista (32/64-bit), XP (32/64-bit) • Mac OS: 10.8, 10.7, 10.6
Resolution	• Up to 1920 x 1080 UXGA
Power Consumption	• 350mA
Optional Power	• 5V DC, 1A (not included)
Dimension	• 97 x 80 x 18.5 mm (3.8 x 3.1 x 0.7 in.)
Weight	• 70 g (2.5 oz.)
Temperature	• Operating: 0° ~ 40° C (32° ~ 104° F) Storage: -10° ~ 80° C (14° ~ 176° F)
Humidity	• Max. 90% (non-condensing)
Certifications	• CE, FCC

System Requirement (For Office use)

Windows XP	• Processor: 1.6GHz Ato mor Celeron • RAM: 512MB
Windows 7/Vista	• Processor: 1.4GHz Core2Duo or better • RAM: 1GB

System Requirement (For Video streaming and playback)

Windows XP	• Processor: 1.8GHz Core2Duo or better • RAM: 1GB
Windows XP	• Processor: 2.4GHz Core2Duo or better • RAM: 2GB • Video Card: Intel® GMA X5400, ATI Radeon™ HD3xxxx, NVidia® GeForce® 9-series or better

NETWORKING SOLUTIONS



PACKAGE CONTENTS

TU2-HDMI
Multi-Language Quick Installation Guide
CD-ROM (Utility & Drivers)
1 x USB cable (45 cm / 18 in.)

RELATED PRODUCTS

TU2-400E	4-Port USB Hub
TU2-H5PI	5-Port USB PCI Adapter
TU2-DVIV	USB to DVI/VGA Adapter

CONTACT INFORMATION

TRENDnet®

20675 Manhattan Place, Torrance, CA 90501 USA
Tel: 1-310-961-5500
Fax: 1-310-961-5511
Web: www.trendnet.com
Email: sales@trendnet.com
1-888-326-6061

