




## 4-Port USB 3.0 Mini Hub


### TU3-H4E (v1.0R)


- Add Four SuperSpeed 5 Gbps USB 3.0 ports
- No CD installation just Plug and Play
- · Backward compatible with USB 2.0 ports
- Reduced clutter with this compact adapter
- No bulky power adapter powered by USB port

TRENDnet's 4-Port USB 3.0 Mini Hub, model TU3-H4E, instantly adds four 5 Gbps SuperSpeed USB 3.0 ports to a computer. No CD installation required-simply plug in flash drives, printers, scanners and other USB 3.0 devices at speeds ten times faster than a USB 2.0 connection. The TU3-H4E is also compatible with older USB 2.0 and 1.1 devices.

# TRENDNET®







#### **USB 3.0**

Easily connect up to four USB 3.0 devices to a USB 3.0 enabled desktop or notebook PC

#### **Supports Most Operating Systems**

Compatible with Windows, Mac, and Linux operating systems

#### **Flexible Connector**

Attached flexible 14 cm (5.5 in.) USB 3.0 cable accommodates most installation scenarios

## **Networking Solution**









#### **Easy Setup**

No CD installation – just Plug and Play



#### **Flexible Connector**

Attached flexible 14 cm (5 in.) USB 3.0 cable accommodates most installation scenarios



#### **Operating Systems**

Compatible with Windows, Mac, and Linux operating systems



#### **LED Indicator**

LED indicator confirms USB connectivity



#### **USB Powered**

No bulky power brick—compact adapter powered by USB port



#### **Backwards Compatibility**

Compatible with USB 2.0 and 1.1 ports



#### SuperSpeed USB 3.0

5 Gbps USB 3.0 ports



#### **Power**

Provides up to 4.5 Watts total power



## **Specifications**

#### Standards

- USB 3.0
- USB 2.0

#### Interfaces

- 1 x Type-A (male) USB 3.0 connector
- 4 x Type-A (female) USB 3.0 ports
- LED indicator

#### **Maximum Data Rate**

• Up to 5 Gbps

#### **Special Features**

- · Compact form factor
- Flexible USB 3.0 connector

#### **Power Consumption**

- USB 3.0: 4.5 Watts total (max.)
- USB 2.0: 2.5 Watts total (max.)

#### **Operating Temperature**

• 0 - 40°C (32 - 104°F)

#### Operating Humidity

· Max. 95% non-condensing

#### Certifications

- CE
- FCC

#### **Dimensions**

- 80 x 37 x 13 mm (3.15 x 1.46 x 0.51 in.)
- 35 g (1.2 oz)

#### Warranty

• 2 year limited

#### **Package Contents**

- TU3-H4E
- · Quick Installation Guide

