



SecurView Wireless N Internet Camera TV-IP110WN(V2.0R)

The SecurView Wireless N Internet Camera (model TV-IP110WN) transmits real-time high quality video over the Internet. Manage your camera from any Internet connection.

Wireless n technology provides unsurpassed wireless coverage and improved streaming video quality. Add this camera to your wireless network at the touch of a button with Wi-Fi Protected Setup (WPS).

Manage up to 32 TRENDnet cameras with the included complimentary camera management software. Advanced features include motion detection recording, email alerts, scheduled recording sessions, MJPEG image compression, and digital zoom. A wall/ceiling mounting kit is included and the off-white camera housing blends into most environments.

FEATURES

- Wi-Fi compliant with IEEE 802.11n standard
- Backwards compatible with IEEE 802.11g, and IEEE 802.11b devices
- One touch WPS connection button
- Power and activity LED indicators (can be disabled)
- Built-in microphone
- 1x 10/100Mbps Fast Ethernet port
- 1 x detachable antenna
- 3x digital zoom
- Dynamic DNS support
- High quality MJPEG video recording
- Support up to 640 x 480 pixels resolution at up to 25 frames per second
- Full screen video mode
- Images controls: Brightness, contrast, saturation and mirror (horizontally/vertical)
- Supports TCP/IP networking, SMTP Email*, HTTP and other Internet protocols
- Record streaming video to your computer
- Advanced encryptions support up to WPA2-RADIUS
- Two adjustable motion detection windows with just-in-time snapshot, triggered video recording, and email alerts
- Included mounting hardware
- Quick Universal Plug and Play (UPnP) installation
- Complimentary SecurView Pro software: manage up to 32 cameras **
- 3-year limited warranty

*Support SSL with complimentary software

**Monitoring multiple cameras may require a high performance CPU

SPECIFICATIONS

Camera	
General	<ul style="list-style-type: none"> • Sensor: 1/4" color CMOS sensor • Resolution: 640 x 480 pixels • Board Lens • Focal Length: 5.0mm • Aperture (F/No): F2.8 • Minimum illumination: 1 Lux • Diagonal viewing angle: 52 degrees
Image & Video	<ul style="list-style-type: none"> • Compression: MJPEG • Exposure/white balance/Gain Control : automatic • Resolution: up to 25fps for VGA (640x480), 25fps for QVGA (320x240), 25fps for QQVGA (160x120)
Audio	<ul style="list-style-type: none"> • Built-in omni-directional microphone • Sensitivity: -48dB +/- 3dB (5 meters max.) • Frequency: 50~16000Hz
Hardware	
Network	<ul style="list-style-type: none"> • IEEE 802.3u 10/100Mbps Fast Ethernet, Auto-MDIX
LED	<ul style="list-style-type: none"> • Power, Link/Act
Reset Button	<ul style="list-style-type: none"> • Restore to factory default
Power Consumption	<ul style="list-style-type: none"> • 5 Watts
Power	<ul style="list-style-type: none"> • 5V, 2.5A external power adapter
Dimension	<ul style="list-style-type: none"> • 70 x 100 x 57mm (2.7 x 3.9 x 3.0 in.)
Weight	<ul style="list-style-type: none"> • Camera: 155g (5.5 oz.) • Stand: 135g (4.8 oz.)
Temperature	<ul style="list-style-type: none"> • Operating: 0°C ~ 45°C (32°F ~ 113°F) • Storage: -15°C ~ 60°C (5°F ~ 140°F)
Humidity	<ul style="list-style-type: none"> • Max. 90% (non-condensing)
Certifications	<ul style="list-style-type: none"> • CE, FCC
Requirement	
Management Interface	<ul style="list-style-type: none"> • Internet Explorer 6.0 or above
To Run SecurView Pro	<ul style="list-style-type: none"> • Windows 7(32/64-bit), Vista(32/64-bit), XP(32/64-bit)
SecurView Pro	<ul style="list-style-type: none"> • Channel: supports up to 32 cameras • Record/Playback/Motion Detection
Network Protocols	<ul style="list-style-type: none"> • TCP/IP, UDP, ICMP, DHCP, NTP, DNS, DDNS, SMTP, FTP, HTTP, PPPoE, UPnP and SSL
Wireless	
Standard	<ul style="list-style-type: none"> • Based on IEEE 802.11n technology • IEEE 802.11g/b compliant
Frequency	<ul style="list-style-type: none"> • 2.4 ~ 2.4835GHz
Antenna	<ul style="list-style-type: none"> • 1 x 2dBi dipole antenna (Reverse-SMA connector)
Date Rate (Auto Fallback)	<ul style="list-style-type: none"> • 802.11n: up to 150Mbps • 802.11g: up to 54Mbps • 802.11b: up to 11Mbps
Security	<ul style="list-style-type: none"> • 64/128-bit WEP, WPA/WPA2-PSK
Output Power	<ul style="list-style-type: none"> • 802.11n: 14 ± 1 dBm • 802.11b: 16 ± 1 dBm • 802.11g: 16 ± 1 dBm
Receiving Sensitivity	<ul style="list-style-type: none"> • 802.11n HT20: -69dBm • 802.11n HT40: -66dBm • 802.11g: -73dBm • 802.11b: -84dBm
Channels	<ul style="list-style-type: none"> • 1~11 (FCC), 1~13(ETSI)
Management	
Remote	<ul style="list-style-type: none"> • Remote management supported
Backup / Restore	<ul style="list-style-type: none"> • Save/retrieve configuration files
Settings	
Image	<ul style="list-style-type: none"> • Brightness, contrast, saturation, flip, mirror (horizontal/vertical)
Video	<ul style="list-style-type: none"> • Encoding type: MJPEG • Resolution: 640 x 480, 320 x 240, 160 x 120 • Frame rate: 1~ 30 fps • Compression: 5 levels
Recording	<ul style="list-style-type: none"> • Recording type: continuous, schedule or motion detection with software
Port Settings	<ul style="list-style-type: none"> • HTTP port: 80 (default)
Digital Zoom	<ul style="list-style-type: none"> • 3x
Dynamic DNS	<ul style="list-style-type: none"> • Yes

SecurView Wireless N Internet Camera

TV-IP110WN(V2.0R)

SPECIFICATIONS

Settings	
Time	• Synchronize with NTP server or set time/date manually
SMTP	• SMTP mail supported up to 2 accounts
System log	• 100 items

NETWORKING SOLUTIONS



PACKAGE CONTENTS

TV-IP110WN

Multi-Language Quick Installation Guide

CD-ROM (Utility & User's Guide)

Camera Stand

Cat. 5 Ethernet cable (1.8 m / 6 ft.)

Power adapter (5V, 2.5A)

RELATED PRODUCTS

TV-IP121WN	SecurView Wireless N Day/Night Internet Camera
TV-IP312WN	SecurView Wireless N Day/Night Internet Camera
TV-IP410WN	SecurView Wireless N Pan/Tilt/Zoom Internet Camera
TV-IP422WN	SecurView Wireless N Day/Night Pan/Tilt/Zoom Internet Camera

CONTACT INFORMATION

TRENDnet

20675 Manhattan Place, Torrance, CA 90501 USA

Tel: 1-310-961-5500

Fax: 1-310-961-5511

Web: www.trendnet.com

Email: sales@trendnet.com

1-888-326-6061

