



TV-IP121W rev: 03.10.2011



## **SecurView Wireless Day/Night Internet Camera** TV-IP121W [A1.0R]

The SecurView Wireless Day/Night Internet Camera (model TV-IP121W) transmits real-time high quality video over the Internet. See and hear people in your camera's viewing field in complete darkness for distances up to 5 meters (16 feet) from any Internet connection.

Manage of up to 16 cameras with complimentary SecurView camera management software. This stylish Internet camera provides crystal clear MJPEG video streams over a secure encrypted wireless connection.

Mount the camera on most surfaces with an included mounting kit. Advanced software features motion detection recording, email alerts\*, scheduled recordings, video viewing options and digital zoom. The camera's brilliant image quality, compact size, audio support and night vision capability make it ideal for your home or office.

#### Features

- Compatible with 802.11g and b wireless networks
- · Compatible with 802.11n wireless networks when set to 802.11n/g/b mixed mode
- · Encryption support for WEP, WPA-PSK and WPA2-PSK standards
- · Infrared lens enables night vision for distances up to 5 meters (16 feet)
- 60 degree viewing angle, 4.5mm focal length and 2.8 F/No
- · Supports still image snapshot to FTP and email\*
- · Record streaming video to your computer
- Supports TCP/IP networking, SMTP email\* and HTTP
- · High quality MJPEG video recording with up to 30 frames per second at 640x480 VGA resolution
- · Motion detection and scheduled recording
- · Control two adjustable motion detection windows with just-in-time snapshot and email notification\* capabilities
- Supports time stamp overlay
- · Hear people in your camera's viewing area through your computer
- Quick Universal Plug and Play installation
- Complimentary SecurView<sup>™</sup> software: view and record up to 16 SecurView cameras simultaneously \*
- Complimentary SecurView<sup>™</sup> software: supports Windows 2000/XP/Vista operating systems
- · 3-year limited warranty
- !\* Does not support SSL
- !\*\* Monitoring multiple cameras may require a high performance CPU and graphics card

### SPECIFICATIONS

Camera		
	Sensor: 1/4" color CMOS sensor     Resolution: 640 x 480 pixels     Focal Length: 4.5mm	
General	• F/No: F2.8 (Board Lens) • Minimum illumination: 0.5 Lux @ F2.8 • View angle: 60 degrees diagonal	
Audio	• Built-in omni-directional microphone • Sensitivity: -48dB +/- 3dB (5 meters max) • Frequency: 50~16000Hz • Codec: PCM	
Image & Video	Compression: MJPEG         • Resolution: VGA (640x480), QVGA (320x240), QQVGA (160x120) up to 30fps         • Exposure/white balance control: automatic         • Flip Images: Vertical/horizontal         • Light Frequency: 50Hz, 60Hz or outdoor	
Hardware		
Network	IEEE 802.3u 10/100Mbps Fast Ethernet, Auto-MDIX	
LED	Power, Link/Act	
IR Wavelength	• 850nm	
Reset Button	Reset settings	
Power Consumption	• 6 watts (max)	
Power	5V DC, 2.5A external power adapter	
Dimension	• 70 x 100 x 57mm (2.67 x 3.94 x 2.95 in.)	
Weight	• Camera: 165g (5.8 oz.) • Stand: 135g (4.76 oz.)	
Temperature	<ul> <li>Operating: 0°C ~ 45°C (32°F ~ 113°F)</li> <li>Storage: -15°C ~ 60°C (14°F ~ 140°F)</li> </ul>	
Certifications	• CE, FCC	
Browser	Internet Explorer	
Requirement (S	ecurView™]	
Camera Configuration	Internet Explorer 6.0 or above	
To Run Software	Windows 2000, XP, Vista	
SecurView <sup>™</sup> Software	Channel: supports up to 16 cameras          • Record/Playback/Motion Detection/Audio	
Wireless		
Standard	• IEEE 802.11b/g	
Antenna	1 x 2dBi detachable Reverse SMA connector	
Security	64/128-bit WEP, WPA-PSK, WPA2-PSK	
Settings		
Image	Brightness, contrast, saturation, sharpness, white balance, flip, mirror (horizontal/vertical)	
Recording	<ul> <li>Recording type: event based (motion detection and digital input trigger), continuous and scheduled</li> <li>Storage size: 32MB (minimum)</li> </ul>	
Snapshot	Trigger event: motion detection      • Action: send alert email and/or upload to FTP	
Port Settings	HTTP port: 80 (default)	
Digital Zoom	• 3x	
Dynamic DNS	• Yes	
Time	Synchronize with NTP server or set time/date manually	

#### NETWORK SOLUTIONS



# PACKAGE CONTENTS

• TV-IP121W
Multi-Language Quick Installation Guide
CD-ROM (Utility & User's Guide)
Cat.5 Ethernet cable (1.8m / 5.9ft)
Mounting kit
Power adapter (5V DC, 2.5A)

#### **RELATED PRODUCTS**

TV-H110	Outdoor Camera Enclosure
TV-IP422W	SecurView Wireless Day/Night Pan/Tilt/Zoom Internet Camera
TV-IP312W	SecurView Wireless Day/Night Internet Camera

#### CONTACT INFORMATION

RENDNET	
675 Manhattan	Place, Torrai

20675 Manhattan Place, Torrance, CA 90501 USA Tel: 1-310-961-5500 Fax: 1-310-961-5511 Web: <u>www.trendnet.com</u> Email: sales@trendnet.com 1-888-326-6061

Т