



Indoor/Outdoor 5MP H.265 WDR PoE Enhanced IR Network Camera

TV-IP1313PI (v1.0R)

- 5MP HD video (2944 x 1656) at 20 fps
- ENHANCED IR LEDs for long range night vision up to 80 meters (262 ft.)
- Outdoor IP67 weather rating
- 120dB Wide Dynamic Range image balancing
- Save installation costs with Power over Ethernet (PoE)
- · Program motion detection recording and email alerts
- Micro SD card slot (up to 128GB)
- Free iOS[®] and Android[™] mobile apps

TRENDnet's Indoor/Outdoor 5MP H.265 WDR PoE ENHANCED IR Network Camera, model TV-IP313PI, provides day and night surveillance with a night vision range of up to 80 meters (262 ft.). ENHANCED IR uses powerful energy efficient infrared LEDs to produce a balanced night vision illumination field and reduces close object overexposure. This network camera delivers year-round surveillance with an IP67 weather rated housing to withstand outdoor environments. Record up to 5MP HD video at 20 fps in a space saving H.265 compression format. View live video with included complimentary software and mobile apps.





Day/Night HD Surveillance Powerful 5MP video in H.265 compression and 80m night vision provides 24-hour surveillance.



Outdoor Ready Built for outdoor environments with an IP67 weather rating and an operating temperature range of -30° – 60° C (-22° – 140° F).



Advanced Night Vision Advanced ENHANCED IR LEDs provide longrange night vision and significantly reduce close object overexposure—common with standard infrared LEDs.

NETWORKING SOLUTION



- Articulating mounting arm and base
- PoE port
- Optional power port (Power adapter not included)
- IP67 weather rated
- 6 Adjustable sun visor
- 6 ENHANCED IR LEDs

TRENDNET

FEATURES



5 Megapixel

Record up to 5MP HD video (2944 x 1656) at 20 fps in the space saving H.265 compression format.



Outdoor Ready Outdoor IP67 weather rated housing



Advanced Playback Advanced in-camera archived video playback functionality



Wide Dynamic Range (WDR) Adjustable 120dB WDR setting improves image quality and focus when a camera is exposed to high contrast lighting environments by

enhancing the dark areas of the image

to make them more visible.



n


ENHANCED IR Night Vision

Advanced ENHANCED IR LEDs provide long-range night vision up to 80m (262 ft.) and significantly reduce close object overexposure—common with standard infrared LEDs.

Adjustable Mounting Base Fully adjustable integrated mounting base provides installation flexibility



Motion Detection Create custom motion detection zones to record video and send email notifications when a zone is triggered.



ONVIF

ONVIF

PoE

Storage

 \square

Save installation costs with Power

Record video to a network storage

device or to a Micro SD card (up to

Create custom tamper detection zones

to send an email notification when the

camera view has been obstructed.

over Ethernet (PoE)

128GB not included).

Tamper Detection

ONVIF Profile S and Profile G



Complimentary Software Complimentary pro-grade software to manage TRENDnet cameras

 1	(
 h	L

Complimentary Apps

recording modes.

Live video to a mobile device with free iOS® and Android™ apps

TRENDNET

SPECIFICATIONS

Lens

- Focal Length: 4mm @ F1.2
- Sensor: 1/2.9" CMOS sensor
- Digital zoom: 4x
- WDR: 120dB

Viewing

- Horizontal angle: 63.5°
- Pan: 0° to 360°
- Tilt: 0° to 90°
- Rotate: 0° to 360°

Minimum Illumination

- IR off: 0.01 lux
- IR on: 0 lux
- IR distance: 80m (262.5 ft.)
- IR wavelength: 850nm

Compression

- H.265+ / H.265
- H.264+ / H.264
- MJPEG

Resolution

- Main stream: H.265+/H.265/H.264+/H.264: 2944 x 1656 up to 20fps
- Sub stream: H.265/H.264/MJPEG: 640 x 360 up to 25fps
- Third stream: H.265/H.264: 1280 x 720 up to 25fps

Hardware Standards

- IEEE 802.1x
- IEEE 802.3
- IEEE 802.3u
- IEEE 802.3x
- IEEE 802.3af

Device Interface

• 10/100Mbps PoE port

Micro SD card slot

- Power jack
- Reset button
- Micro SD slot
- Supports Micro SD/SDHC/SDXC (not included)
- Up to 128GB

Housing

• IP67 weather rated

Network Protocol

- IPv4, IPv6, UDP, TCP/IP
- DHCP, NTP, DDNS, SMTP, FTP, LLTD
- SNMP v1, v2c, v3, QoS/DSCP, IEEE 802.1X
- NFS, SMB/CIFS
- HTTP, HTTPS
- PPPoE
- UPnP, RTSP, RTP

Compliant Standard

• ONVIF (Profile S, Profile G)

Management Interface

- Multi-language support: English, French, German, Spanish, and Portuguese
- Image settings: Brightness, Contrast, Saturation, Sharpness, Exposure Time, image Gain, Day/Night switch. Smart Supplement Light (Smart IR), BLC, WDR, white balance, Digital Noise Reduction, Mirror, Rotate, Scene Mode, Video Standard
- WDR enhances video quality in high contrast daytime lighting
- Digital Noise Reduction removes digital noise from the video signal
- Recording: to computer, or SAMBA share
- Time, date, and text overlay
- IP Address Filter
- Video Recording: scheduled, motion detection, and tamper detection
- Motion detection: define up to three motion detection areas and motion sensitivity
- Video masks: define custom video masks
- Tamper detection function: email notification
- Snapshot: real time snapshot and motion triggered
- Supported dynamic DNS services: dyn.com and no-ip.com
- Supports remote management

All references to speed are for comparison purposes only. Product specifications, size, and shape are subject to change without notice, and actual product appearance may differ from that depicted herein.

20675 Manhattan Place • Torrance • CA 90501 • USA • T: 1-888-326-6061 • F: 1-310-961-5511 • intlsales@trendnet.com • www.TRENDnet.com TRENDnet is a registered trademark. Other Brands and product names are trademarks of their respective holders. Information provided in this document pertain to TRENDnet products and is subject to change at

any time, without notice. For the most recent product information please visit http://www.trendnet.com. Copyright © TRENDnet. All Rights Reserved.

 Compatible browsers: Chrome[™] or Firefox® (live view resolution up to 1280 x 720), Internet Explorer® (live view resolution up to 2944 x 1656)

Dimension

• 300 x 105 x 105mm (11.8 x 4.1 x 4.1 in.)

TV-IP1313PI

Weight

• 1.2kg (2.64 lb.)

Operating Temperature

• -30° - 60° C (-22° - 140° F)

Humidity

• Max. 95% non-condensing

Power

- Input: PoE
- Max. consumption: 12.5W

Power Adapter (optional model: 12VDC1A)

- Input: 100 240V AC , 50/60Hz
- Output: 12V DC, 1A external power adapter

TRENDnet Mira VMS

- Supports TRENDnet cameras
- Set recording options (motion detection, schedule, event trigger)
- Search and playback
- · Custom viewing modes and options
- Compatibility: Windows® and Mac®

TRENDnet Mira App

- Free iOS® and Android™ apps
- View live camera video
- Push notifications
- Take snapshots and videos
- Playback
- · Share live view to family members or friends

Certifications

- CE
- FCC

Warranty

3 year

Package Contents • TV-IP1313PI

Weather seal

· Quick installation guide

· Camera mounting hardware

Updated: 6/29/2020