



## Internet Camera Server with Audio TV-IP201

TV-IP201 Internet Camera Server with Audio is the perfect device for remote monitoring and transmitting real-time events over the Internet. The TV-IP201 functions as a video/audio/surveillance camera allowing you to view live events with your web browser via Internet or Intranet. Up to 32 cameras can be remotely managed with the bundled IP View software. This Internet Camera Server has VGA quality streaming video, automatic image capture, and event notification via e-mail, making it the ideal solution for Internet video broadcasting applications.

### FEATURES

- Supports M-JPEG Compression and Audio Monitoring
- Built-in RS-485 connectors for Pan & Tilt control device (additional Pan & Tilt control device required)
- Supports ActiveX Control for Internet Explorer and Java applet for Internet Explorer and Netscape Navigator
- Allows for Remote Access from Web Browser for Live Image Viewing and listening
- Supports TCP/IP networking, SMTP e-mail, HTTP and other Internet related protocols
- Supports Web Configuration with Password Protection
- Powerful Windows IPView Application Software for multiple cameras monitoring, motion detection alerts, image capturing, and video recording (Windows 98/ME/2000/XP)
- Built-in I/O Ports to Trigger Alarm and Email Notification
- Broad Range of Applications for Monitoring Homes, Offices, Banks, Hospitals, and a Variety of Private and Public Monitoring
- 3-year limited warranty

# Internet Camera Server with Audio

## TV-IP201

### SPECIFICATIONS


Image Sensor	
Sensor	• 1/4" Color CMOS Sensor
Resolution	• 640 x 480 pixel
Lens	• f :6.0mm F1.8 Lens (CS-Mount Standard, Replaceable)
Minimum Illumination	• On: 2.5 Lux • Off: 2.5 Lux
Audio	
MIC Input	• Internal MIC (mono)
Volume Control	• Adjustable
Compression	• ADPCM/PCM
Video/Image	
Display Standard	• 30fps@CIF, QVGA, VGA
Compression	• M-JPEG
Resolution / Light Frequency	• 176 x 144, 320 x 240, 640 x 480 • Outdoor/Indoor/50Hz/60Hz
Frame Rate Setting	• 1, 3, 7, 12, 15, 25, 30 (Depends on video format)
Mirror Function	• Vertical / Horizontal
Control	• Yes (Brightness/ Contrast/ Saturation/ Sharpness)
Communication	
LAN	• 10/100Mbps Auto-Sense, Auto-MDIX
Protocol	• HTTP, FTP, TCP/IP, UDP, ARP, ICMP, DHCP, PPPoE, DDNS, SMTP, UPnP
Software	
Browser	• Internet Explorer (5.0 or above) or Netscape Navigator (6.0 or above)
Application	• IPView Software and Active X Plug-In
Supported OS	• Windows 98SE, ME, 2000, XP, Vista
System	
CPU	• RDC1610
RAM/Flash ROM	• 16MB/4MB
OS	• Linux
IO & Control	
Input	• 1 set, 2 pin (photo relay; Active High: 9~40V DC; Dropout: 0V DC)
Output	• 1 set, 2 pin (photo relay. Close circuit current: 70mA~100mA; 30Ohm. Open circuit voltage: 240V AC or 350V DC)
RS-485	• Half Duplex (to control external pan/tilt device)
Requirements	
Memory Size	• 512MB or above • Intel Celeron 1.1GHz or above (Pentium 4 Recommend) VGA card resolution: 800 x 600 or above Note: According to Engineer, to record 8 Cameras at the same time, will require at least P4 3.0GHz, 1GB RAM.

# Internet Camera Server with Audio TV-IP201

## SPECIFICATIONS

Physical/Environmental	
Dimension	• 180 x 83 x 47 mm (7.1 x 3.3 x 1.9 in.)
Weight	• Camera: 247 g (8.7 oz.); Stand: 116 g (4.1 oz.)
Stand Height	• 128 mm (4.7 in.)
Power	• 5V DC, 2.5A External Adapter
Consumption	• 4.5 Watt max.
Temperature	• Operating: 5° C ~ 40° C (41° F ~ 104° F)      • Storage: -25° C ~ 50° C (-13° F ~ 122° F)
LED	• Power: Blue      • Link/Active: Orange
Humidity	• 5% ~ 95% Non-Condensing
Safety Emissions	• CE, FCC

## NETWORKING SOLUTIONS



## PACKAGE CONTENTS

- TV-IP201
- Utility CD-ROM
- Multi-Language Quick Installation Guide
- RJ-45 Ethernet Cable
- Power Adapter (5V DC 2.5A)

## RELATED PRODUCTS

TV-IP100	Internet Camera Server
TV-IP100W	Wireless Internet Camera Server
TV-IP201W	Wireless Internet Camera Server with Audio
TV-IP300	Advanced Day/Night Internet Camera Server
TV-IP300W	Advanced Wireless Day/Night Internet Camera Server

## ORDERING INFORMATION

### TRENDnet®

20675 Manhattan Place, Torrance, CA 90501 USA  
 Tel: 1-310-961-5500  
 Fax: 1-310-961-5511  
 Web: [www.trendnet.com](http://www.trendnet.com)  
 Email: [sales@trendnet.com](mailto:sales@trendnet.com)

To Order Please Call:

**1-888-326-6061**

