



Indoor / Outdoor 4 MP PoE Dome Day / Night Network Camera

TV-IP315PI (v1.1R)

- 4 MP Full HD resolution
- Compact IP66 weather rated housing
- IK10 vandal proof protection
- Night vision up to 30 m (100 ft.)
- Save installation costs with Power over Ethernet (PoE)
- Program motion detection recording and email alerts
- Wide Dynamic Range image balancing
- ONVIF and IPv6 support

The Indoor / Outdoor 4 MP PoE Dome Day / Night Network Camera, model TV-IP315PI, provides powerful 4-megapixel night vision in complete darkness for up to 30 meters (100 ft.) Even in extreme environments, this ultra-compact camera will function all year, thanks to an IP66 weather rated housing. Use the included pro-grade software to manage up to 32 TRENDnet cameras or download the free iOS[®] or Android[™] mobile app.




Power over Ethernet (PoE)

PoE offers cost savings and the flexibility to install this compact dome camera in the desired location.



Day/Night HD Surveillance

Powerful 4 MP video at 20 fps in H.264+ compression (2 MP 1080p at 30 fps) and 30 m rated night vision provide 24-hour surveillance.



Outdoor Ready

Built for extreme environments with an IP66 weather rating and an operating temperature range of -30 – 60 °C (-22 – 140 °F).

Networking Solution



- ① Mounting base
- ② IP66 housing
- ③ IR LEDs
- ④ PoE port
- ⑤ Power port

Hardware



Compact Fixed Dome

Manually pan and tilt 75° to set the camera's final viewing field



PoE

Save installation costs with Power over Ethernet (IEEE 802.3af)



Outdoor Ready

Outdoor IP66 weather rated and an operating temperature range of -30 – 60 °C (-22 – 140 °F)



Vandal Resistant

Impact protection rated with IK10

Performance



4 Megapixel

Record 2688 x 1520 pixel video at 20 fps in H.264+ compression



Night Vision

Night vision up to 30 m (100 ft.) in complete darkness



Smart IR

Dynamic IR adjustment optimizes night visibility



WDR

120 dB Wide Dynamic Range improves video quality in high contrast lighting environments

Camera Management



Multi-Language Interface

Support for English, French, Spanish, German, and Portuguese



Advanced Playback

Advanced in-camera archived video review functionality



Storage

SMB / CIFS support with notification if storage drive is full



Motion Detection

Create motion detection windows with separate sensitivity settings and event triggers



Recording Schedule

Define a weekly recording schedule



Tamper Detection

Receive tamper detection video clips via email



IPv6

IPv6 support



ONVIF / PSIA

ONVIF (Profile S, Profile G) and PSIA compliant



Free Apps

See live video on a mobile device with free iOS® and Android™ apps



Complimentary Software

Complimentary pro-grade software to manage up to TRENDnet 32 cameras

Specifications

Lens

- Focal length: 4 mm, F2.0
- Focal depth: 20 cm +
- Lens: fixed focus
- Sensor: 1/3" progressive scan CMOS
- DNR: 3D DNR
- WDR: 120 dB
- Zoom: user define zoom area

Viewing Angle

- Horizontal: 83°
- Vertical: 45°
- Diagonal: 98°

Minimum Illumination

- IR off : 0.01 lux
- IR on: 0 lux
- Built-in IR cut filter
- 30 m IR illumination distance
- Smart IR

Video Resolution

- H.264, H.264+: 2688 x 1520 up to 20 fps (1920 x 1080 up to 30 fps)
- H.264/MJPEG: 640 x 360 up to 30 fps

Hardware Standards

- IEEE 802.1X
- IEEE 802.3
- IEEE 802.3u
- IEEE 802.3x
- IEEE 802.3af

Device Interface

- 10/100 Mbps PoE port
- Power port (for non-PoE installations, adapter sold separately)
- Reset button

Network Protocol

- IPv4, IPv6, UDP, TCP, ICMP, ONVIF Profile S and Profile G, PSIA
- DHCP, NTP, DNS, DDNS, SMTP, FTP, SNMP (v1, v2c, v3)
- NFS, SMB / CIFS
- HTTP, HTTPS

- PPPoE
- UPnP, Bonjour, RTSP, RTP, RTCP, SSL

Operating Temperature

- -30 – 60 °C (-22 – 140 °F)

Operating Humidity

- Max. 95% non-condensing

Certifications

- CE
- FCC

Dimensions

- 110 x 110 x 90 mm. (4.3 x 4.3 x 3.5 in.)

Weight

- 476 g (1.05 lb.)

Power

- Input: PoE (802.3af)
- Consumption: 5 Watts max.

Optional Power Supply (Sold separately)

- Input: 100 – 240 V AC 50/60 Hz 0.5 A
- Output: 12 V DC 1 A
- 5.5 mm barrel connector
- TRENDnet power adapter, model 12VDC1A (not included)

Management Interface

- Multi-language support: English, French, German, Spanish and Portuguese
- IP address filter
- QoS traffic prioritization
- Time, date, and text overlay
- Image settings: brightness, contrast, hue, sharpness, Denoise 3D, Shutter time, sense-up, Saturation, AGC (automatic gain control), flip, day/night mode, white balance
- WDR enhances video quality in high contrast daytime lighting
- 2D Digital Noise Reduction enhances night vision quality
- Recording: to computer, NAS, SAMBA, or through software
- Video Recording: scheduled, motion detection, sound detection, and tamper detection

- Motion detection: define up to three motion detection areas and motion sensitivity
- Privacy masks: define custom privacy mask up to 3 areas
- Tamper detection function: email notification, FTP, SD card, or Samba server if the viewing field darkens suddenly
- Network disconnection fallback: set to automatically save video to Micro SD card (sold separately) if connection to network is broken
- Snapshot: real time snapshot, sound detection, and motion detection
- Services DNS dynamiques supportés: dyn.com, no-ip.com et iptecno.com
- Management Setting: maximum 21 user accounts
- Supports remote management
- Compatible browsers: Chrome™ or Firefox® (live view resolution up to 640 x 360), Internet Explorer® or Safari® (live view resolution up to 1920 x 1080)

TRENDnetVIEW EVO Software

- Supports up to 32 TRENDnet cameras
- Multiple language support
- Set recording options (motion detection, schedule, event trigger)
- Search and playback
- Custom viewing modes and options
- Compatibility: Windows® 10, 8.1, Windows Server® 2012, 2008

TRENDnet IPView App

- Free iOS® and Android™ app
- View live camera video on a mobile device
- Take snapshots
- Zoom

Warranty

- 3 year limited

Package Contents

- TV-IP315PI
- CD-ROM (Utility Software & User's Guide)
- Quick Installation Guide
- Camera mounting hardware

