



## 300Mbps Concurrent Dual Band Wireless N Router TEW-671BR(V1.0R)

The 300Mbps Concurrent Dual Band Wireless N Router provides wireless n speed, coverage and reliability with up to 12x the speed and 4x the coverage of a wireless g connection\*.

Concurrent Dual Band technology creates two separate wireless n networks at the same time—one on the 2.4GHz frequency and the other on the less congested 5GHz frequency.

Wirelessly stream HD multimedia content using the uncongested 5GHz frequency, while surfing the Internet using the 2.4GHz frequency. Multiple Input Multiple Output (MIMO) antenna technology reduces wireless dead spots. Wi-Fi Protected Setup (WPS) integrates other WPS supported devices quickly. Advanced wireless encryption secures your valuable data and WMM® Quality of Service (QoS) technology prioritizes gaming, Internet calls and video streams.

### FEATURES

- IEEE 802.11n draft 2.0 and IEEE 802.11a/b/g compliant
- Transmits simultaneous 2.4Ghz and 5Ghz Wireless Local Area Network (WLAN) signals (with separate default SSIDs)
- 4 x 10/100Mbps Auto-MDIX LAN ports and 1 x 10/100Mbps WAN port (Internet)
- Compatible with most popular cable/DSL Internet service providers using Dynamic/Static IP, PPPoE and PPTP
- High-speed data rates up to 300Mbps using an IEEE 802.11n draft 2.0 connection
- 2 external antennas provide high-speed performance and expansive wireless coverage
- Monitor wireless bandwidth information and allocation
- Multiple SSID with wireless or wired/wireless clients isolation support
- Advanced Firewall protection with Network Address Translation (NAT) and Stateful Packet Inspection (SPI)
- Access restriction with Internet Access Control; time scheduling, IP, URL and MAC filtering
- Built in pre-configured virtual servers and Application Level Gateway services for special Internet applications
- Universal Plug and Play (UPnP) for auto discovery and support for device configuration of Internet applications
- Multiple pass-through sessions for popular VPN applications (IPSec and PPTP)
- Applications priority queue, IP range bandwidth allocation and Wi-Fi Multimedia (WMM) provide advanced QoS support
- Easy setup via Web browser using the latest versions of Internet Explorer, FireFox, Chrome, and Safari
- One touch wireless security setup using the Wi-Fi Protected Setup (WPS) button
- Complete wireless security with WPA/WPA2, WPA-PSK/WPA2-PSK, and WEP
- Works with Windows, Linux and Mac operating systems
- 3 year limited warranty

\*Maximum wireless signal rates are referenced from IEEE 802.11 theoretical specifications. Actual data throughput and coverage will vary depending on interference, network traffic, building materials and other conditions.

# 300Mbps Concurrent Dual Band Wireless N Router

TEW-671BR(V1.0R)

## SPECIFICATIONS

### Hardware

Standards	<ul style="list-style-type: none"><li>• Wired: IEEE 802.3 (10Base-T), IEEE 802.3u (100Base-TX)</li><li>• Wireless: IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n (draft 2.0) • IEEE 802.1d Spanning Tree</li></ul>
WAN	<ul style="list-style-type: none"><li>• 1 x 10/100Mbps Auto-MDIX port (Internet)</li></ul>
LAN	<ul style="list-style-type: none"><li>• 4 x 10/100Mbps Auto-MDIX port</li></ul>
WPS Button	<ul style="list-style-type: none"><li>• Wi-Fi Protected Setup (WPS) with other WPS compliant devices</li></ul>
Connection Type	<ul style="list-style-type: none"><li>• Dynamic IP, Static (fixed) IP, PPPoE, PPTP</li></ul>
Router/ Firewall	<ul style="list-style-type: none"><li>• Enable/disable Firewall • NAT, SPI and DoS (block ping, port scan, sync flood)</li><li>• ALG support (enable/disable support) – RTP/RTSP, AOL, FTP, ICMP, WMP/MMS, NetMeeting, SIP MAC / IP filtering (deny or allow)</li><li>• UPnP, DMZ, Static/Dynamic Route support</li></ul>
WDS	<ul style="list-style-type: none"><li>• Enable/disable Wireless Distribution System support</li></ul>
LED Indicator	<ul style="list-style-type: none"><li>• Power, LAN1~LAN4, WAN, 2.4GHz WLAN, 5GHz WLAN, WPS</li></ul>
Power Adapter	<ul style="list-style-type: none"><li>• 12V DC, 1A external power adapter</li></ul>
Power Consumption	<ul style="list-style-type: none"><li>• 900mA (max)</li></ul>
Dimension (L x W x H)	<ul style="list-style-type: none"><li>• 170 x 111 x 26 mm (6.7 x 4.4 x 1 inches)</li></ul>
Weight	<ul style="list-style-type: none"><li>• 320g (0.7 lb)</li></ul>
Temperature	<ul style="list-style-type: none"><li>• Operation: 0°~ 45°C (32°F~ 113°F) • Storage: -10°~ 70°C (14°F~158°F)</li></ul>
Humidity	<ul style="list-style-type: none"><li>• Max. 95% (non-condensing)</li></ul>
Certifications	<ul style="list-style-type: none"><li>• CE, FCC</li></ul>

### Wireless

Frequency	<ul style="list-style-type: none"><li>• 2.412 ~ 2.484GHz • 5.150~5.250GHz; 5.725~5.825GHz (FCC) • 5.150~5.250MHz (ETSI)</li></ul>
Antenna	<ul style="list-style-type: none"><li>• 2 x 2dBi fixed dipole antenna • 2 x 4dBi internal antennas</li></ul>
Module Technique	<ul style="list-style-type: none"><li>• OFDM: BPSK, QPSK, 16-QAM, 64-QAM • DBPSK, DQPSK, CCK</li></ul>
Data Rate	<ul style="list-style-type: none"><li>• 802.11a: 54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 9Mbps and 6Mbps</li><li>• 802.11b: 11Mbps, 5.5Mbps, 2Mbps, and 1Mbps</li><li>• 802.11g: 54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 9Mbps and 6Mbps</li><li>• 802.11n: up to 300Mbps</li></ul>
Security	<ul style="list-style-type: none"><li>• 64/128-bit WEP, WPA-PSK(TKIP)/WPA2-PSK(AES), WPA/WPA2-RADIUS • 802.1x Authenticator</li><li>• Multiple SSID and SSID disable/isolation support • Isolation between wireless or wireless/wired clients for each SSID</li></ul>
QoS	<ul style="list-style-type: none"><li>• Priority queue, bandwidth allocation support and WMM</li></ul>
Output Power	<ul style="list-style-type: none"><li>• 802.11a: 14dBm (typical) • 802.11b: 17dBm (typical) • 802.11g: 14dBm (typical)</li><li>• 802.11n: 15dBm (typical) with HT20 or HT40</li></ul>
Receiving Sensitivity	<ul style="list-style-type: none"><li>• 802.11a: -75dBm (typical) @ 54Mbps • 802.11b: -91dBm (typical) @ 11Mbps</li><li>• 802.11g: -75dBm (typical) @ 54Mbps • 802.11n: -75dBm (typical) with HT20 or HT40</li></ul>
Channel	<ul style="list-style-type: none"><li>• 2.4GHz : 1~11 (FCC), 1~13 (ETSI) • 5GHz : following local regulations</li></ul>

# 300Mbps Concurrent Dual Band Wireless N Router

TEW-671BR(V1.0R)

## NETWORKING SOLUTIONS



## PACKAGE CONTENTS

- TEW-671BR
- Multi-Language Quick Installation Guide
- CD-ROM (User's Guide)
- Cat.5 Ethernet cable (1m / 3.2ft)
- Power adapter (12V, 1A)

## RELATED PRODUCTS

TEW-664UB	300Mbps Dual Band Wireless N USB Adapter
TEW-624UB	300Mbps Wireless N USB 2.0 Adapter

## ORDER INFORMATION

**TRENDNET**<sup>®</sup>

20675 Manhattan Place, Torrance, CA 90501 USA  
Tel: 1-310-961-5500  
Fax: 1-310-961-5511  
Web: [www.trendnet.com](http://www.trendnet.com)  
Email: [sales@trendnet.com](mailto:sales@trendnet.com)  
1-888-326-6061

